

MINITERMS
Female Disconnects
F SERIES

FEATURES

VINYL:

Electro tin plated copper, 600V, 105 °C. Female, quick disconnect, Vinyl



UN-INSULATED-BARE:

Electro tin plated copper, 600V, 105 °C. Female quick disconnect



NYLON:

Turned up edges give this disconnect more safety and reliability. 600V, 105 °C, Nylon



STYLE	INSULATION TYPE	WIRE RANGE	STUD SIZE	CERTIFICATION VARIANCE
Female	Vinyl	22-18	0.110	
Female	Vinyl	22-18	0.110	UL
Female	Vinyl	22-18	0.187	
Female	Vinyl	22-18	0.187	UL
Female	Vinyl	22-18	0.250	
Female	Vinyl	16-14	0.110	UL
Female	Vinyl	16-14	0.110	UL
Female	Vinyl	16-14	0.187	
Female	Vinyl	16-14	0.187	
Female	Vinyl	16-14	0.250	
Female	Vinyl	12-10	0.250	
Female	Un-insulated	22-18	0.110	UL
Female	Un-insulated	22-18	0.110	UL
Female	Un-insulated	22-18	0.187	UL
Female	Un-insulated	22-18	0.187	UL
Female	Un-insulated	22-18	0.250	
Female	Un-insulated	16-14	0.110	UL
Female	Un-insulated	16-14	0.110	
Female	Un-insulated	16-14	0.187	UL
Female	Un-insulated	16-14	0.187	UL
Female	Un-insulated	16-14	0.250	
Female	Un-insulated	12-10	0.250	
Female	Un-insulated	8	0.250	NON-UL
Female	Nylon	22-18	0.110	NON-UL
Female	Nylon	22-18	0.110	UL
Female	Nylon	22-18	0.187	UL
Female	Nylon	22-18	0.187	UL
Female	Nylon	22-18	0.250	
Female	Nylon	16-14	0.110	UL
Female	Nylon	16-14	0.110	UL
Female	Nylon	16-14	0.187	UL
Female	Nylon	16-14	0.187	
Female	Nylon	16-14	0.250	
Female	Nylon	12-10	0.250	

"S" PACKS

PRO PACKS

STD PACKS

BULK PACKS

L (IN)	W (IN)	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY	CAT. NO.	QTY
0.728	0.125	-	-	-	-	F22-110-2V	100	F22-110-2V-BULK	1000
0.789	0.170	-	-	-	-	F22-110-3V	100	F22-110-3V-BULK	1000
0.748	0.196	-	-	-	-	F22-187-2V	100	F22-187-2V-BULK	1000
0.789	0.250	-	-	-	-	F22-187-3V	100	F22-187-3V-BULK	1000
0.826	0.259	F22-250-3V-S	25	F22-250-3V-P	80	F22-250-3V	100	F22-250-3V-BULK	1000
0.789	0.170	-	-	-	-	F16-110-2V	100	F16-110-2V-BULK	1000
0.789	0.170	-	-	-	-	F16-110-3V	100	F16-110-3V-BULK	1000
0.748	0.196	F16-187-2V-S	25	-	-	F16-187-2V	100	F16-187-2V-BULK	1000
0.748	0.196	-	-	-	-	F16-187-3V	100	F16-187-3V-BULK	1000
0.826	0.259	F16-250-3V-S	25	F16-250-3V-P	70	F16-250-3V	100	F16-250-3V-BULK	1000
0.925	0.259	F12-250-3V-S	-	F12-250-3V-P	50	F12-250-3V	50	F12-250-3V-BULK	500
0.550	0.150	-	-	-	-	F22-110-2	100	F22-110-2-BULK	1000
0.554	0.150	-	-	-	-	F22-110-3	100	F22-110-3-BULK	1000
0.565	0.233	-	-	-	-	F22-187-2	100	F22-187-2-BULK	1000
0.565	0.233	-	-	-	-	F22-187-3	100	F22-187-3-BULK	1000
0.629	0.259	-	-	F22-250-3-P	100	F22-250-3	100	F22-250-3-BULK	1000
0.557	0.149	-	-	-	-	F16-110-2	100	F16-110-2-BULK	1000
0.531	0.125	-	-	-	-	F16-110-3	100	F16-110-3-BULK	1000
0.556	0.233	-	-	-	-	F16-187-2	100	F16-187-2-BULK	1000
0.559	0.233	-	-	-	-	F16-187-3	100	F16-187-3-BULK	1000
0.629	0.259	-	-	F16-250-3-P	125	F16-250-3	100	F16-250-3-BULK	1000
0.669	0.259	-	-	-	-	F12-250-3	50	F12-250-3-BULK	500
0.665	0.320	-	-	-	-	F8-250-3	50	F8-250-3-BULK	1000
0.789	0.163	-	-	-	-	F22-110-2N	100	F22-110-2N-BULK	1000
0.789	0.210	-	-	-	-	F22-110-3N	100	F22-110-3N-BULK	1000
0.789	0.125	-	-	-	-	F22-187-2N	100	F22-187-2N-BULK	1000
0.789	0.125	-	-	-	-	F22-187-3N	100	F22-187-3N-BULK	1000
0.866	0.259	-	-	-	-	F22-250-3N	100	F22-250-3N-BULK	1000
0.789	0.163	-	-	-	-	F16-110-2N	100	F16-110-2N-BULK	1000
0.789	0.163	-	-	-	-	F16-110-3N	100	F16-110-3N-BULK	1000
0.789	0.238	-	-	-	-	F16-187-2N	100	F16-187-2N-BULK	1000
0.787	0.196	-	-	-	-	F16-187-3N	100	F16-187-3N-BULK	1000
0.866	0.259	-	-	-	-	F16-250-3N	100	F16-250-3N-BULK	1000
0.944	0.259	-	-	-	-	F12-250-3N	50	F12-250-3N-BULK	500