

# LOCKOUT / TAGOUT Self-Adhesive Labels and Spiral Wrap VL, DSS, SR SERIES



## FEATURES

- Self-adhesive labels are sub-surface printed polyester labels.
- Rigid signs are available in either polycarbonate or polyester material.

### CAUTION

In Accordance with OSHA Standard 1910.147, All Equipment, Machines and Processes Shall Be Locked Out Prior to Servicing. Lockout Procedures are Posted in the Main Operating Area and/or by the Main Energy Source of Each Machine. If You Have any Questions About the Lockout Procedures, Please See Your Supervisor or the Safety Director. This Standard Will Be Strictly Enforced.

CAT. NO.	LEGEND	SIZE (IN.)	STD. CTN. QTY.
<b>VL-4</b>	Remove All Doubt. Lock it Out.	2 1/4 x 4 1/2	25
<b>VL-7</b>	Warning Potential Arc-Flash Hazards Exist While Working on this Energized Equipment	2 1/4 x 4 1/2	25
<b>DSS-5</b>	High Voltage	10 x 14	25
<b>DSS-6</b>	High Voltage Keep Out	10 x 14	25

## SPIRAL WRAP

- Permits flexible routing of cable harnesses while forming a neat, protective bundle.
- Twists on easily and allows lead-outs at any point.

### POLYETHYLENE

- For general indoor use with good resistance to ordinary solvents and abrasion.

### UV POLYETHYLENE

- Ultraviolet resistance for general outdoor use with good resistance to ordinary solvents and abrasion.

### NYLON

- For use in wider temperature ranges with high resistance to abrasion and good solvent resistance.



CAT. NO.	COLOR	MATERIAL	O.D.	I.D.	BUNDLE RANGE	LENGTH (FT.)	STD. CTN. QTY.
<b>SRPE-250</b>	Natural	Polyethylene	0.236	0.157	0.157 - 1.97	100	1
<b>SRPE-375</b>	Natural	Polyethylene	0.393	0.295	0.295 - 2.36	100	1
<b>SRPE-500</b>	Natural	Polyethylene	0.472	0.354	0.354 - 2.56	100	1
<b>SRPE-2500</b>	Black	UV Polyethylene	0.236	0.157	0.157 - 1.97	100	1
<b>SRPE-3750</b>	Black	UV Polyethylene	0.393	0.295	0.295 - 2.36	100	1
<b>SRPE-5000</b>	Black	UV Polyethylene	0.472	0.354	0.354 - 2.56	100	1