

# H362AWC

Safety switch, heavy duty, fusible, 60A, 600 VAC/VDC, 3 poles, 50 hp, NEMA 12K, crouse hinds arktite



## Main

Product	Receptacle Switch
For Use With	Plug APJ6485 Crouse-Hinds Arktite
Current Rating	60 A
Enclosure Rating	NEMA 3R/12 galvanized steel
Horsepower Rating	15 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 30 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 15 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 50 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 10 hp at 250 V DC conforming to NEC 240.6
Disconnect Type	Fusible disconnect switch
Short Circuit Current Rating	200 KA 10 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Electrical Connection	Receptacle
Certifications	UL Listed
Voltage Rating	600 V AC 250 V DC
Wire Configuration	4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

## Complementary

Tightening torque	45 Lbf.In (5.08 N.m) AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) AWG 8) 35 lbf.in (3.95 N.m) AWG 14...AWG 10)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Maximum Depth	7 in (177.80 mm)

## Ordering and shipping details

Category	00118 - H&HU SW,W/C-HINDS RECPT-WC
Discount Schedule	DE1
GTIN	00785901195573
Nbr. of units in pkg.	1
Package weight(Lbs)	27.28 lb(US) (12.37 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.70 in (19.558 cm)
Package 1 width	14.00 in (35.56 cm)
Package 1 Length	33.20 in (84.328 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	15

Package 2 Weight	437.00 lb(US) (198.22 kg)
Package 2 Height	42.00 in (106.68 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------