H365DS

Safety switch, heavy duty, fusible, 400A, 3 poles, 250 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel





Main

Product	Single Throw Safety Switch
Current Rating	400 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 1/0750 kcmil copper or aluminium
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Factory Installed Neutral	None
Electrical Connection	Lugs
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 4/4X/5 stainless steel 304

Complementary

o in promontary	
Maximum Horse Power Rating	100 Hp at 480 V AC 5060 Hz for 3 phases motors conforming to NEC 240.6 250 Hp at 480 V AC 5060 Hz for 3 phases motors conforming to NEC 430.52 125 Hp at 600 V AC 5060 Hz for 3 phases motors conforming to NEC 240.6 350 Hp at 600 V AC 5060 Hz for 3 phases motors conforming to NEC 430.52 50 Hp 250 V DC 50 hp 600 V DC
Width	26.25 in (666.75 mm)
Height	46.25 in (1174.75 mm)
Maximum Depth	10.13 in (257.30 mm)
Tightening torque	62.14 N.m (AWG 1/0750 kcmil)

Ordering and shipping details

Category	00055 - H&HU SW,NEMA4&5,400-1200A
Discount Schedule	DE1
GTIN	00785901195900
Nbr. of units in pkg.	1
Package weight(Lbs)	185 lb(US) (83.91 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	13.11 in (33.3 cm)	
Package 1 width	26.69 in (67.8 cm)	
Package 1 Length	50.98 in (129.5 cm)	

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫ _{Yes}
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

18 months