8502SDO2V08



Main

Product or component type	Contactor
Range of product	8502S
Control circuit	Common control circuit
[Uc] control circuit voltage	208 V AC 60 Hz
Contactor application	Non-reversing
Line Rated Current	45 A
Poles description	3P
Phase	3 phases
Rated power in HP	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
System Voltage	600 V AC
Control type	No control units
•	
Local signalling	No indicator
Local signalling Auxiliary contact composition	No indicator Without
Auxiliary contact composition	Without
Auxiliary contact composition Provided equipment	Without Fuse not supplied
Auxiliary contact composition Provided equipment Electrical connection	Without Fuse not supplied Screw clamp terminals
Auxiliary contact composition Provided equipment Electrical connection NEMA degree of protection	Without Fuse not supplied Screw clamp terminals Not rated (open device) CSA
Auxiliary contact composition Provided equipment Electrical connection NEMA degree of protection Product certifications	Without Fuse not supplied Screw clamp terminals Not rated (open device) CSA UL listed
Auxiliary contact composition Provided equipment Electrical connection NEMA degree of protection Product certifications NEMA size	Without Fuse not supplied Screw clamp terminals Not rated (open device) CSA UL listed 2

Complementary

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 1545 - Schneider Electric declaration of conformity	Compliant - since 1545 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period 18 months
