# Product data sheet Characteristics

# XB2BN4161 pushbutton 600VAC 10A 22mm XB2 +options

Product availability: Stock - Normally stocked in distribution facility

Price\*: 200.00 USD



#### Main

| Range of product              | Harmony XB2           |  |
|-------------------------------|-----------------------|--|
| Product or component type     | Push-button           |  |
| Device presentation           | Complete mechanism    |  |
| Device short name             | XB2B                  |  |
| Bezel material                | Chromium plated metal |  |
| Mounting diameter             | 0.87 in (22 mm)       |  |
| Sale per indivisible quantity | 1                     |  |
|                               |                       |  |

## Complementary

| _   |  |  |  |
|---|--|--|--|
|   |  |  |  |
|   |  |  |  |
|   |  |  |  |
| Main  |  |  |  |
| Range of product                            | Harmony XB2  |  |  |
| Product or component type                   | Push-button  |  |  |
| Device presentation                         | Complete mechanism   |  |  |
| Device short name                           | XB2B   |  |  |
| Bezel material                              | Chromium plated metal  |  |  |
| Mounting diameter                           | 0.87 in (22 mm)  |  |  |
| Sale per indivisible quantity               | 1  |  |  |
|   |  |  |  |
| 0   |  |  |  |
| Complementary                               | Maharan hatta da                 |  |  |
| Specificity of operator                     | Mushroom button head   |  |  |
| Control type                                | Illuminated push-button  |  |  |
| Terminals description ISO n°1               | (13-14)NO<br>(21-22)NC   |  |  |
| Shape of signaling unit head                | Round  |  |  |
| Type of operator                            | Maintained   |  |  |
| Operator profile                            | Mushroom Ø 40 mm, cap/operator or lens colour:red (unmarked marking) |  |  |
| Contacts type and composition               | 1 NO + 1 NC  |  |  |
| [lth] conventional free air thermal current | 10 A conforming to EN/IEC 60947-5-1                                  |  |  |
| [Ui] rated insulation voltage               | 600 V 3 conforming to EN/IEC 60947-1                                 |  |  |
|   |  |  |  |
| Ordering and shipping details               |  |  |  |
| Category                                    | 22461 - PUSHBUTTON, 22MM_(METAL)                                     |  |  |
| Discount Schedule                           | CS2  |  |  |
| GTIN  | 00785901675471   |  |  |
| Nbr. of units in pkg.                       | 1  |  |  |
| Package weight(Lbs)                         | 0.280000000000003  |  |  |
| An. 05, 2047                                |  |  |  |

## Ordering and shipping details

| Category              | 22461 - PUSHBUTTON, 22MM_(METAL) |  |  |
|-----------------------|----------------------------------|--|--|
| Discount Schedule     | CS2                              |  |  |
| GTIN                  | 00785901675471                   |  |  |
| Nbr. of units in pkg. | 1                                |  |  |
| Package weight(Lbs)   | 0.2800000000000003               |  |  |

| Returnability     | Υ  |  |
|-------------------|----|--|
| Country of origin | FR |  |
|                   |    |  |

#### Contractual warranty

| Warranty period | 18 months      |
|-----------------|----------------|
| Trainanty ponou | - Commentation |