

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Load Center
Range of product	QO
Load center type	Main breaker
Line Rated Current	125 A
Number of spaces	6
Short-circuit current	22 kA
Number of circuits	12
Number of tandem circuit breakers	6
Phase	1 phase
System Voltage	120/240 V AC

Complementary

AWG gauge	AWG 4...AWG 2/0 (aluminium/copper)
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Feed-thru lugs
Device composition	Grounding bar (ordered separately)
Electrical connection	Feed-thru lugs
Wiring configuration	3-wire
Material	Tin plated copper busbar
Enclosure material	Welded galvanized steel
Surface finish	Baked enamel grey
Box number	3R
Product certifications	UL listed
Height	481 mm
Width	14.76 in (375 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901868163
Nbr. of units in pkg.	1
Package weight(Lbs)	22.309999999999999
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1411 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------