

Product availability : Stock - Normally stocked in distribution facility



Price* : 390.00 USD



Main

Range of product	8501X
Relay type	Utility
Product or component type	Relay
[In] rated current	10 A AC 5 A DC
Contacts type and composition	4 NO 4 standard contact cartridges
Poles description	4P
[Uc] control circuit voltage	125 V DC
Maximum switching voltage	250 V DC
Mounting support	Panel
Ambient air temperature for operation	-40...160 °F
Electrical connection	Screw clamp terminals
Product certifications	CE CSA UL listed
Operating time	37 ms pick-up 21 ms drop-out

Ordering and shipping details

Category	21157 - 8501 XDO (DC)
Discount Schedule	CP2
GTIN	00785901743316
Nbr. of units in pkg.	1
Package weight(Lbs)	3.2600000000000002
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1332 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------