Product data sheet Characteristics

QO2401021

QO Miniature Circuit Breaker 40A 2P 120/240V 10kA Plug-in Mount, Shunt Trip

Product availability: Stock - Normally stocked in distribution facility





Price*: 256.00 USD



Main

| Main | | ž |
|--------------------------------|---------------------------|---|
| Product or component type | Miniature circuit-breaker | 50 |
| Range of product | QO | |
| Line Rated Current | 40 A | ‡ 5 |
| System Voltage | 120/240 V AC 48 V DC | in a la company de la company |
| Mounting mode | Plug-in | |
| Poles description | 2P | ti d |
| Circuit breaker type | Standard | |
| Circuit breaker application | HACR rated | <u></u> |
| Electrical connection | Box lugs | , - |
| Accessory / separate part type | Shunt trip, AC, | 7 |
| | | |

Complementary

| Complementary | | |
|---------------------------|--|----------|
| Breaking capacity | 10 kA at: 120/240 V AC 5 kA at: 48 V DC | |
| Number of spaces required | 3 | |
| AWG gauge | AWG 8AWG 2 (copper or aluminium) | <u>,</u> |

Environment

| Product certifications | UL listed CSA |
|---------------------------------------|------------------|
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| Category | 00004 - QO,QOT 10-30A 1P;10-60A 2P |
|-------------------|-------------------------------------|
| | 00004 - QO,QOT 10-00A II ,10-00A ZI |
| Discount Schedule | DE2A |

| GTIN | 00785901493983 |
|-----------------------|-------------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.920000000000004 |
| Returnability | Υ |
| Country of origin | MX |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------------|---|---|
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity | |
| | Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| | Reference not containing SVHC above the threshold | |
| Product environmental profile | Available | |
| Product end of life instructions | Need no specific recycling operations | - |

Contractual warranty

| Warranty period | 18 months |
|-----------------|-----------|
| | |