Product data sheet Characteristics

QOB3301021

QO Miniature Circuit Breaker 30A 3P 240V 10kA Bolt-on Mount, Shunt Trip

Product availability: Stock - Normally stocked in distribution facility





Price*: 482.00 USD



Main

| Widiri | | <u> </u> |
|--------------------------------|---------------------------|------------------------|
| Product or component type | Miniature circuit-breaker | - |
| Range of product | QO | |
| Line Rated Current | 30 A | * |
| System Voltage | 240 V AC 48 V DC | ## # # # # |
| Mounting mode | Bolt-on | |
| Poles description | 3P | |
| Circuit breaker type | Standard | |
| Circuit breaker application | HACR rated | |
| Electrical connection | Pressure plate | , |
| Accessory / separate part type | Shunt trip, AC, | |
| | | |

Complementary

| Complementary | | |
|---------------------------|--|----------|
| Breaking capacity | 5 kA at: 48 V DC 10 kA at: 240 V AC | |
| Number of spaces required | 4 | |
| AWG gauge | AWG 14AWG 8 (copper or aluminium) | ģ |

Environment

| Product certifications | UL listed CSA |
|---------------------------------------|------------------|
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | | _ |
|-------------------|------------------------------|-------|
| Category | 00015 - QOB CIRCUIT BREAKERS | ēr: I |
| Discount Schedule | DE2 | claim |

| GTIN | 00785901494409 |
|-----------------------|------------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.18999999999999 |
| Returnability | Υ |
| Country of origin | MX |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity |
| | Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold |
| | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| Warranty period 18 months |
|---------------------------|
|---------------------------|