
In the world of power transmission and distribution, look to Hubbell

# Catalog Home

## **Product Datasheet**

CHANCE

## M140T23 -- Type T (ANSI) Cutout Fuselink



140 amp, Type T (ANSI) Cutout fuselink with a 23" (584.2mm) pigtail.

Product Specifications	
Туре	Fuselinks
Fuselinks	Type T (ANSI)
Amp Rating	140
Removable Buttonhead	No
Pigtail Length	23" (584.2mm)
Twin Pigtails (140A and 200A only)	No
PDF Catalog Page	Click <u>HERE</u> to view detailed PDF Catalog
Fuse Link Application Guide and Time-Current Curves	Click <u>HERE</u> and request, Fuse Links (Bulletin 10-7701).
Fuse Element	Copper
Required Cutout Fuseholder	200 Amp (Do not use in a 100 amp fuseholder.)
Material Type	Non-Standard
UPC Code	09635904339
Standard Package	5
Standard Package Unit	Each
Min Order Qty	5
Pallet Quantity	2400
Weight / Ea.	0.245 lbs

#### **Notes**

Can not be used with an arc-shortening rod in fuseholder.

## **Compressed Product Number**

M140T23

Catalog Home



# Warranty Info | Trademarks | Terms of Use

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.