# SAFETY DATA SHEET

### 1. Identification

**Product identifier Upside Down Marking Paints - Alert Orange** 

Other means of identification

18204 Product code Recommended use Coating Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name **Address** 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

**General Information** 215-674-4300 **Technical** 800-521-3168

**Assistance** 

800-272-4620 **Customer Service** 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com

# 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1

> Gases under pressure Liquefied gas Carcinogenicity Category 2

Aspiration hazard Category 1

Hazardous to the aquatic environment, **Environmental hazards** Category 3

long-term hazard

**OSHA** defined hazards Not classified.

Label elements

**Health hazards** 



Signal word Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. Suspected of causing cancer.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear

protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a physician/poison center immediately. Do NOT induce vomiting. If exposed or

concerned: Get medical attention.

Storage Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose or store at

temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

Harmful to aquatic life with long lasting effects.

Supplemental information

53.89% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Material name: Upside Down Marking Paints - Alert Orange

# 3. Composition/information on ingredients

ixtuioo			
Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	20 - 30
Calcium carbonate		1317-65-3	10 - 20
n-Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Solvent naphtha (petroleum), light aliph.		64742-89-8	10 - 20
Distillates (petroleum), hydrotreated light		64742-47-8	1 - 5
Titanium dioxide		13463-67-7	< 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical Skin contact

attention if irritation develops and persists.

**Eve contact** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, Ingestion

keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis.

Most important

symptoms/effects, acute and

delayed

**Mixtures** 

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

Direct contact with eyes may cause temporary irritation.

protect themselves.

## 5. Fire-fighting measures

Small Fires: Powder. Water spray. Carbon dioxide (CO2). Dry sand. Suitable extinguishing media

Large Fires: Water spray. Alcohol resistant foam.

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment

and precautions for firefighters

Fire-fighting

equipment/instructions

General fire hazards

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Extremely flammable aerosol.

# 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

**Environmental precautions** 

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

## Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

## Conditions for safe storage, including any incompatibilities

0

Level 3 Aerosol.

Store locked up. Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

## 8. Exposure controls/personal protection

Components	for Air Contaminants (29 CFR 1910.1000)  Type	Value	Form
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction
,		15 mg/m3	Total dust.
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit	t Values		
Components	Туре	Value	
n-Butane (CAS 106-97-8)	STEL	1000 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide t	o Chemical Hazards		
Components	Туре	Value	Form
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
n-Butane (CAS 106-97-8)	TWA	1900 mg/m3	
,		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
ological limit values	No biological exposure limits noted for the ing	redient(s).	
·		* *	

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as nitrile or rubber. Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Air monitoring is needed to Respiratory protection

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

#### **Appearance**

Liquid. **Physical state** Aerosol. **Form** Orange. Color Aromatic. Odor Odor threshold Not available. Not available. pН -138.8 °F (-94.9 °C) Melting point/freezing point

Initial boiling point and boiling

range

-47.2 °F (-44 °C)

-2.2 °F (-19 °C) Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

1.5 %

Flammability limit - upper

(%)

10.9 %

2221.9 hPa estimated Vapor pressure

Vapor density > 1 (air = 1)Relative density 0.77 - 0.85Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

410 °F (210 °C) estimated **Auto-ignition temperature** 

Not available. **Decomposition temperature** Not available. **Viscosity (kinematic)** 

Percent volatile 75 %

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials. Incompatible materials Strong oxidizing agents. Acids. Fluorine. Chlorine. Nitrates.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

Ingestion May be fatal if swallowed and enters airways.

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

# Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

**Product Species Test Results** 

Upside Down Marking Paints - Alert Orange

**Acute** 

Dermal

LD50 Rabbit 25990.8555 mg/kg estimated

Inhalation

LC50 Rat 8179.4048 mg/l, 15 Minutes estimated **Product Species Test Results** 

Oral

LD50 Rat 90459.0625 mg/kg estimated

Chronic

Oral

LD50 Mouse 2626.2632 g/kg estimated

Skin corrosion/irritation

6351.3516 mg/l, 4 hours estimated

Serious eye damage/eye

Prolonged skin contact may cause temporary irritation.

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization

Not available.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Suspected of causing cancer.

Titanium dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

Not classified.

repeated exposure

**Aspiration hazard** 

May be fatal if swallowed and enters airways.

Prolonged inhalation may be harmful. **Chronic effects** 

IARC Monographs. Overall Evaluation of Carcinogenicity

# 12. Ecological information

otoxicity	Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.			
Product		Species	Test Results	
Upside Down Marking	Paints - Alert Oran	ige		
Acute				
Crustacea	EC50	Daphnia	9545.4541 mg/l, 48 hours estimated	
Fish	LC50	Fish	15568.5059 mg/l, 96 hours estimated	
Components		Species	Test Results	
Distillates (petroleum)	, hydrotreated light	(CAS 64742-47-8)		
Acute				
	EC50	Invertebrate (saltwater)	4720 mg/l, 96 hours	
Aquatic				
Acute				
Fish	LC50	Bluegill (Lepomis macrochirus)	1740 mg/l, 96 hours	
		Fathead minnow (Pimephales promela	as) 45 mg/l, 96 hours	
Titanium dioxide (CAS	3 13463-67-7)			
Aquatic				

EC50 > 1000 mg/l, 48 hours Crustacea Water flea (Daphnia magna) Fish LC50 Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

n-Butane 2.89 Propane 2.36

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Material name: Upside Down Marking Paints - Alert Orange

1055 Version #: 01 Issue date: 10-01-2013

# 13. Disposal considerations

Disposal of waste from residues / unused products

This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Empty container can be recycled. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with

local/regional/national regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Do not re-use empty containers.

# 14. Transport information

DOT

UN number UN1950

UN proper shipping name Transport hazard class(es) Aerosols, flammable, limited quantity

Class 2.1 Subsidiary risk -

Label(s) 2.1
Packing group Not applicable.

Special precautions for user Not available.

Special provisions N82

Packaging exceptions 306

Packaging non bulk 304

IATA

UN number UN1950

**UN proper shipping name** Aerosols, flammable, limited quantity

None

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Not available.

Other information

Packaging bulk

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only Allowed.

**IMDG** 

UN number UN1950

**UN proper shipping name** AEROSOLS, LIMITED QUANTITY

Transport hazard class(es)
Class

Class 2 Subsidiary risk -

Packing group Not applicable.

**Environmental hazards** 

Marine pollutantNo.EmSF-D, S-USpecial precautions for userNot available.

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

## **CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-Butane (CAS 106-97-8) Propane (CAS 74-98-6)

**Safe Drinking Water Act** 

(SDWA)

Not regulated.

(ODIIA)

Food and Drug Not regulated.

Administration (FDA)

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

#### **US** state regulations

#### US. New Jersey RTK - Substances: Listed substance

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

### **US. Massachusetts RTK - Substance List**

Calcium carbonate (CAS 1317-65-3)

n-Butane (CAS 106-97-8) Propane (CAS 74-98-6)

## US. Pennsylvania RTK - Hazardous Substances

Calcium carbonate (CAS 1317-65-3)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Titanium dioxide (CAS 13463-67-7)

#### **US. Rhode Island RTK**

n-Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004
Titanium dioxide (CAS 13463-67-7) Listed: September 2, 2011

## Volatile organic compounds (VOC) regulations

EPA

Aerosol coatings (40 Compliant

CFR 59, Subpt. E)

State

Aerosol coatings This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for

sale in all 50 states.

Maximum incremental 0.58

reactivity (MIR)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

# 16. Other information, including date of preparation or last revision

Issue date10-01-2013Prepared byAllison ChoVersion #01

Further information Not available.

HMIS® ratings Health: 1\*
Flammability: 4

Physical hazard: 0 Personal protection: B Health: 1

NFPA ratings
Health: 1
Flammability: 4
Instability: 0

Disclaimer
The information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries.

1055 Version #: 01 Issue date: 10-01-2013 8 / 8

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).