

Pin and Sleeve Devices/Mechanical Interlocks

Performance

Electrical

Dielectric Withstand Voltage	3000V AC.
Max. Working Voltage	600V RMS (i.e., minimum creepage distance 10 millimeters, minimum clearance 8 millimeters, per IEC 60309-1 for devices rated over 500V).
Current Interrupting	Certified for current interrupting at full rated current (Except DC rated devices).
Temperature Rise	Max. 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Endurance	5,000 connect and disconnect cycles with load for 16A and 20A, 1,000 cycles with load and 1,000 cycles without load for 30A, 32A, 60A and 63A, and 250 cycles with load and 250 cycles without load for 100A and 125A.

Mechanical

Impact Resistance	Per CSA C22.2 No. 182.1 / UL1682.
Cord Grip Cable Retention	Per CSA C22.2 No. 182.1 / UL1682.
Cord Accommodation	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49 and the harmonized <HAR> European Standards.
Terminal Identification	Terminals identified in accordance with North American and IEC conventions.
Product Identification	Identification and ratings are a permanent part of the device housing.

Environmental

Moisture Resistance	Watertight per IEC 60309-1.
Ingress Protection	TYPE 4X, 12 and IP69K.
Flammability	V.0.
Operating Temperatures	Maximum Continuous 75°C; Minimum - 40°C without impact.

Materials

Housings	PBT.
All Other Materials	Resistant to corrosion and chemical attack.

Note: Specification sheets for all other Pin and Sleeve catalog numbers are available upon request.

Horsepower Ratings for Hubbell IEC Pin and Sleeve Devices*

Single Phase

Amps	Wire Count	Voltage	Clock	Catalog Number	HP Rating
20	3	125V	4	HBL320x4W	1
20	3	250V	6	HBL320x6W	2
20	3	480V	7	HBL320x7W	5
20	4	125/250 (208L-L)	12	HBL420x12W	2
20	4	125/250 (250L-L)	12	HBL420x12W	2
20	4	125/250 (125L-N)	12	HBL420x12W	1
30	3	125V	4	HBL330x4W	2
30	3	250V	6	HBL330x6W	3
30	3	480V	7	HBL330x7W	7.5
30	3	550VDC	8	HBL330X8	N/A
30	4	125/250 (208L-L)	12	HBL430x12W	3
30	4	125/250 (250L-L)	12	HBL430x12W	3
30	4	125/250 (125L-N)	12	HBL430x12W	2
60	3	125V	4	HBL360x4W	2
60	3	250V	6	HBL360x6W	3
60	3	480V	7	HBL360x7W	7.5
60	3	250VDC	3	HBL360x3W	N/A
60	3	550VDC	8	HBL360x8W	N/A
60	4	125/250 (208L-L)	12	HBL460x12W	3
60	4	125/250 (250L-L)	12	HBL460x12W	3
60	4	125/250 (125L-N)	12	HBL460x12W	2
100	3	125V	4	HBL3100x4W	5
100	3	250V	6	HBL3100x6W	15
100	3	480V	7	HBL3100x7W	30
100	3	250VDC	3	HBL3100x3W	N/A
100	3	550VDC	8	HBL3100x8W	N/A
100	4	125/250 (208L-L)	12	HBL4100x12W	10
100	4	125/250 (250L-L)	12	HBL4100x12W	15
100	4	125/250 (125L-N)	12	HBL4100x12W	5

3-Phase

Amps	Wire Count	Voltage	Clock	Catalog Number	HP Rating
20	4	3Ø 250V	9	HBL420x9W	5
20	4	3Ø 480V	7	HBL420x7W	10
20	4	3Ø 600V	5	HBL420x5W	10
20	4	3Ø 380-415V	6	HBL420x6W	7.5
20	5	3ØY 120/208V	9	HBL520x9W	3
20	5	3ØY 277/480V	7	HBL520x7W	10
20	5	3ØY 347/600V	5	HBL520x5W	10
20	5	3Ø 240/415V	6	HBL520x6W	5
30	4	3Ø 250V	9	HBL430x9W	7.5
30	4	3Ø 480V	7	HBL430x7W	15
30	4	3Ø 600V	5	HBL430x5W	20
30	5	3ØY 120/208V	9	HBL530x9W	5
30	5	3ØY 277/480V	7	HBL530x7W	15
30	5	3ØY 347/600V	5	HBL530x5W	20
30	4	3Ø 380/415V	6	HBL430x6W	10
30	5	3Ø 200/346-240/415	6	HBL530x6W	10
60	4	3Ø 250V	9	HBL460x9W	7.5
60	4	3Ø 480V	7	HBL460x7W	20
60	4	3Ø 600V	5	HBL460x5W	25
60	4	3Ø 380-415VAC	6	HBL460x6W	10
60	5	3ØY 120/208V	9	HBL560x9W	7.5
60	5	3ØY 277/480V	7	HBL560x7W	20
60	5	3ØY 347/600V	5	HBL560x5W	25
60	5	3Ø 200/346-240/415	6	HBL560x6W	10
100	4	3Ø 250V	9	HBL4100x9W	15
100	4	3Ø 480V	7	HBL4100x7W	40
100	4	3Ø 600V	5	HBL4100x5W	50
100	4	3Ø 380-415V	6	HBL4100x6W	30
100	5	3ØY 200/346-240/415V	6	HBL5100x6W	30
100	5	400VDC	8	HBL5100x8W	N/A
100	5	3ØY 120/208V	9	HBL5100x9W	15
100	5	3ØY 277/480V	7	HBL5100x7W	40
100	5	3ØY 347/600V	5	HBL5100x5W	50

Note: *Horsepower Ratings are NOT standardized amongst different Pin and Sleeve manufacturers.