ATD2000C

Dual (Ultrasonic and Passive Infrared) Ceiling Sensors

Combines the excellent minor motion detection of ultrasonic with the outstanding passive infrared (PIR) long-range major motion detection.

Description	Voltage	Coverage Area: 2000 sq. ft. (360°)	Coverage Area: 1000 sq. ft. (180°)
Low voltage sensor with photocell and isolated relay.	24V DC	**ATD2000CRP**	**ATD1000CRP**
Low voltage sensor.	24V DC	**ATD2000C**	**—**
Line voltage sensor.	120-277V AC	**ATD2000CL**	**ATD1000CL**

ATD1000CRP

Passive Infrared Ceiling Sensors

Outstanding long range major motion detection.

Description	Voltage	Coverage Area: 1500 sq. ft. (360°)
Low voltage sensor with photocell and isolated relay.	24V DC	**ATP1500CRP**
Low voltage sensor.	24V DC	**ATP1500C**
Line voltage sensor.	120-277V AC	**ATP1500CL**

Note: All Low voltage ceiling sensors must use a CU series control unit. See page E-10 for details.
Line voltage ceiling sensors suitable for occupancy (auto-on) applications only. Use low voltage ceiling sensors and low voltage switches with CU series control units (E-10) for vacancy (manual on) applications.
See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics.
For Assembled in USA units Add suffix "U".

ATP1500C

ATD1600WRP

Dual (Ultrasonic and Passive Infrared) Wall Mount Sensors

Description	Color	Coverage	Catalog Number
Low voltage sensor 32kHz with photocell and isolated relay.	Office White	1600 sq. ft.	**ATD1600WRP**

ATP1600WRP

Passive Infrared Wall Mount Sensors

Description	Color	Coverage	Catalog Number
Low voltage sensor with photocell and isolated relay.	Office White	1600 sq. ft.	**ATP1600WRP**
Low voltage sensor for aisle and high bay applications, with photocell and isolated relay.	Office White	120 linear feet	**ATP120HBRP**

Note: All wall mount sensors must use a CU series control units. See page E-10 for details.
See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics.
For Assembled in USA units Add suffix "U"

DSL30W1
DSM30W1

Low Voltage Switches

Single gang design, momentary or latching operation. Compatible with all Hubbell low voltage sensors and Load:Logic® Centralized and Distributed Control Systems. 100mA @ 30V DC max.

Description	Color	Catalog Number
Low voltage switch, latching, 1 button.	Ivory	**DSL30I1**
	Light Almond	**DSL30LA1**
	White	**DSL30W1**
Low voltage switch, momentary, 1 button.	Ivory	**DSM30I1**
	Light Almond	**DSM30LA1**
	White	**DSM30W1**
Low voltage switch, momentary, 2 buttons.	Ivory	**DSM30I2**
	Light Almond	**DSM30LA2**
	White	**DSM30W2**

Note: Wallplate sold separately.