

PHOTOCONTROLS

Flush Mount

Lexan® Housing

3000 Series



SPECIFICATIONS

- **ON/OFF:** Turn ON is 1 to 5fc, Turn OFF is 3 to 15fc.
- **Time Delay:** ON and OFF.
- **Cell:** Cadmium sulphide, conformal coated 1/2" diameter.
- **Contacts:** Normally closed.
(The unit fails in the ON position).
- **Lead Wires:** Three color coded, minimum 9" wire leads, #16AWG, rated for 105 °C.
- **Power Consumption:** Averages under 1 watt.
- **Temperature Range:** -40 °F to +140 °F (-40 °C to +60 °C).
- **Fail Mode:** ON.
- **Warranty:** 5 years.

APPLICATIONS

- Pole lanterns.
- Lawn lighting.
- Walkways.

FEATURES

- **Sensor:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.
- **Operation:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.
- **Standards:** Meets ANSI/UL773A.
- **Housing:** Control housing is weather-resistant molded Lexan® with ultrasonically welded seams.
- **Model 3000:** Flush mounting through .6875" hole in post lantern or lighting fixture, 3/8" NPT, stem 3/4" long. Gasket and nut supplied.
- **Model 3010:** Flush mounting into standard, raintight junction box. Includes aluminum plate and gasket to fit FS type outdoor junction box.
- **Energy Savings:** Works with screw base CFLs.



CAT. NO.	CERTIFICATION	UPC CODE	VOLTAGE VAC 50/60Hz	RATING		
				TUNGSTEN	BALLAST	LED
3000	cULus	60020	120	2000W	1800VA	600VA
3002	cULus	60019	208-277	3470-4620W	2080-2770VA	1040-1385VA
3006	CSA	60026	347	5760W	3470VA	-
3010	cULus	60021	120	2000W	1800VA	600VA