



**ATD2000C**

## Dual (Ultrasonic and Passive Infrared) Ceiling Sensors

Combines the excellent minor motion detection of ultrasonic with the outstanding passive infrared (PIR) long-range major motion detection.

Description	Voltage	Coverage Area	
		2000 sq. ft. (360°)	1000 sq. ft. (180°)
Low voltage sensor with photocell and isolated relay.	24V DC	<b>ATD2000CRP</b>	<b>ATD1000CRP</b>
Low voltage sensor.	24V DC	<b>ATD2000C</b>	—
Line voltage sensor.	120-277V AC	<b>ATD2000CL</b>	<b>ATD1000CL</b>



**ATD1000CRP**

## Passive Infrared Ceiling Sensors

Outstanding long range major motion detection.

Description	Voltage	Coverage Area
		1500 sq. ft. (360°)
Low voltage sensor with photocell and isolated relay.	24V DC	<b>ATP1500CRP</b>
Low voltage sensor.	24V DC	<b>ATP1500C</b>
Line voltage sensor.	120-277V AC	<b>ATP1500CL</b>

*Note: All Low voltage ceiling sensors must use a CU series control unit. See page E-10 for details.*

*Line voltage ceiling sensors suitable for occupancy (auto-on) applications only. Use low voltage ceiling sensors and low voltage switches with CU series control units (E-10) for vacancy (manual on) applications.*

*See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics.*

*For Assembled in USA units Add suffix "U".*



**ATP1500C**

## Dual (Ultrasonic and Passive Infrared) Wall Mount Sensors

Description	Color	Coverage	Catalog Number
Low voltage sensor 32kHz with photocell and isolated relay.	Office White	1600 sq. ft.	<b>ATD1600WRP</b>



**ATD1600WRP**

## Passive Infrared Wall Mount Sensors

Description	Color	Coverage	Catalog Number
Low voltage sensor with photocell and isolated relay.	Office White	1600 sq. ft.	<b>ATP1600WRP</b>
Low voltage sensor for aisle and high bay applications, with photocell and isolated relay.	Office White	120 linear feet	<b>ATP120HBRP</b>



**ATP1600WRP**

*Note: All wall mount sensors must use a CU series control units. See page E-10 for details.*

*See pages E-25 to E-28 for technical specifications, coverage patterns and wiring schematics.*

*For Assembled in USA units Add suffix "U"*

## Low Voltage Switches

Single gang design, momentary or latching operation. Compatible with all Hubbell low voltage sensors and Load:Logic® Centralized and Distributed Control Systems. 100mA @ 30V DC max.

Description	Color	Catalog Number
Low voltage switch, latching, 1 button.	Ivory	<b>DSL3011</b>
	Light Almond	<b>DSL30LA1</b>
	White	<b>DSL30W1</b>
Low voltage switch, momentary, 1 button.	Ivory	<b>DSM3011</b>
	Light Almond	<b>DSM30LA1</b>
	White	<b>DSM30W1</b>
Low voltage switch, momentary, 2 buttons.	Ivory	<b>DSM3012</b>
	Light Almond	<b>DSM30LA2</b>
	White	<b>DSM30W2</b>



**DSL30W1**  
**DSM30W1**

*Note: Wallplate sold separately.*