



## Features

- Shielded
- Super neutral
- K factor 20, copper wound
- Surge Suppression
- Branch circuit protection
- Integral bonding
- Open or enclosed NEMA 1 and 3R designs
- Floor mount



## Power System Supply Assemblies

KVA	Phase	Input	Cycles	Branch Circuit Output	Circuits	Mounting	Catalog Number
15	3-ph	575/480/400V AC	50/60 Hz	20A 208/120V AC	3	Floor	<b>P150CUNV208F</b>

Note: Additional custom configurations are possible. Consult factory for wall or rack mount options.

## LINKOSITY® Specifications

### Certifications

System Level	ETL Classified to NEC
Component Assemblies	
PSDA	UL Listed
PSSA	Listed to UL508A
Connecting Components	Listed to UL2238 and UL 50
Cable (Up to 22AWG)	UL 300V Type ITC/PLTC 105°C
Cable (16AWG and Up)	UL 600V Type TC-ER, MTW 90°C or STOOW 600V 105°C

### Performance

#### Electrical

Voltage	Up to 600V
Amperage	Up to 30A

#### Environmental

##### Connectivity System Components

Moisture Resistance	UL Type 4, 4X, 12 and 13
Ingress Protection	IP67 Suitability
Flammability	UL94HB Cables/UL94V-0 receptacles

##### Power System Distribution Assemblies

Moisture Resistance	NEMA Type 1, Type 3R, Type 4X
---------------------	-------------------------------

##### Power System Supply Assemblies

Moisture Resistance	NEMA Type 3R
---------------------	--------------