

Rating					Unfused Circuit-Lock® Devices		Reverse Service	
Amps	Poles and Wires	Configuration Recept.	Plug	AC Voltage	Mechanical Interlock	Mating Plug	Mechanical Interlock	Mating Plug
20	3P 4W			120/240V			—	—
	3P 4W			3Ø 240V			—	—
	3P 4W			3Ø 480V			—	—
	3P 4W			3Ø 600V			—	—
30	2P 3W			120V			—	—
	2P 3W			240V			—	—
	2P 3W			480V			—	—
	3P 4W			120/240V			—	—
	3P 4W			3Ø 240V				
	3P 4W			3Ø 480V				
	3P 4W			3Ø 600V				
	4P 5W			3ØY 120/208V			—	—
	4P 5W			3ØY 277/480V			—	—
	4P 5W			3ØY 347/600V			—	—
32	3P 4W			380V 50HZ-440V 60HZ			—	—
60	2P 3W			120V			—	—
	2P 3W			240V			—	—
	2P 3W			480V			—	—
	3P 4W			120/240V				
	3P 4W			3Ø 240V				
	3P 4W			3Ø 480V				
	3P 4W			3Ø 600V				
	4P 5W			3ØY 120/208V			—	—
	4P 5W			3ØY 277/480V			—	—
	4P 5W			3ØY 347/600V			—	—
100	2P 3W			240V			—	—
	3P 4W			120/240V				
	3P 4W			3Ø 240V				
	3P 4W			3Ø 480V				
	3P 4W			3Ø 600V				
	4P 5W			3ØY 120/208V			—	—

Note: 20, 30 and 32A – 1 inch NPT hub supplied; 60 and 100A – 1¼ inch hub supplied.