

**IP66**  
SUITABILITY

Enclosure Type 4X, 12

Rating						Fused Circuit-Lock® Devices	
Amps	Poles and Wires	Configuration Recep./ Conn.	Plug/ Inlet	AC Voltage	Mechanical Interlock	Mating Plug	
30	3P 4W			120/240V			
	3P 4W			3Ø 240V			
	3P 4W			3Ø 480V			
	3P 4W			3Ø 600V			
	4P 5W			3ØY 277/480V			
60	3P 4W			120/240V			
	3P 4W			3Ø 240V			
	3P 4W			3Ø 480V			
	3P 4W			3Ø 600V			
	4P 5W			3ØY 120/208V			

Note: 30A – 1 inch NPT hub supplied; 60A – 1¼ inch hub supplied.



HBL430MIF12W

Gray Style Switch



HBLACFSNO

HBL30MIFRS

Black Style Switch

## Replacement Auxiliary Contacts

Description	Black Style Switch Catalog Number	Gray Style Switch Catalog Number
Auxiliary contact, normally open, A600 pilot duty, break before break.	<b>ACFSNO</b>	<b>HBLACFSNO</b>
Auxiliary contact, normally closed, A600 pilot duty, break before break.	<b>ACFSNC</b>	<b>HBLACFSNC</b>

Note: Auxiliary contacts are specific to the style switch noted and are NOT interchangeable. All new installations are shipped with gray style switch.



ACFSNO

## Replacement Switches

Description	Gray Style Switch Catalog Number
For 30A fused switches.	<b>HBL30MIFRS</b>
For 60A fused switches. Gray Style switch will retro fit Black Style switch.	<b>HBL60MIFRS</b>



MICPK30

## Watertight Closure Plug Kits

Description	Catalog Number
For 30A Circuit-Lock® unfused and fused Pin and Sleeve mechanical interlocks.	<b>MICPK30</b>
For 60 and 100A Circuit-Lock® unfused and fused Pin and Sleeve mechanical interlocks.	<b>MICPK60</b>



CA3430MI

## Replacement Flip Covers

Description	Catalog Number
For 30A, 3 and 4 wire mechanical interlocks.	<b>CA3430MI</b>
For 30A, 5 wire mechanical interlocks.	<b>CA530MI</b>
For 60A mechanical interlocks.	<b>CA60MI</b>



HBLRFT2

## Replacement Mounting Feet

Description	Catalog Number
Replacement mounting feet and screws for 30 and 60A fused mechanical interlocks.	<b>HBLRFT2<sup>Δ</sup></b>

Note: <sup>Δ</sup>Package of 10 feet and 10 screws.