

15 Amp Straight Blade Devices and Accessories

MARINE PRODUCTS

CC
SECTION



15A 125V
NEMA 5-15R
UL/CSA



15A 125V AC Straight Blade Devices

Description	Catalog Number
Yellow corrosion-resistant/weather resistant duplex receptacle. Use outdoors or where salt and other corrosive materials are a problem. Accepts 15A 125V, 2 pole 3 wire straight blade plugs. IP20 suitability.	HBL52CM62
Same as HBL52CM62 except ivory in color.	HBL52CM62I
Single version of HBL52CM62 duplex yellow receptacle. IP20 suitability.	HBL52CM61
Yellow Insulgr [®] plug has rugged nylon housing and detachable cord grip with range of .23-.72 in. (5.8-18.3) that utilizes a unique offset jaws arrangement for secure strain relief. IP20 suitability.	HBL52CM66C
Yellow Insulgr [®] connector body has rugged nylon housing and detachable cord grip with range of .23-.72 in. (5.8-18.3) that utilizes a unique offset jaws arrangement for secure strain relief. IP20 suitability.	HBL52CM69C
Yellow Valise [®] plug has one-piece nylon housing that assembles easily with two screws. Built-in cord grip has range of .22-.66 in. (5.6-16.8). IP20 suitability.	HBL52CM66V
Yellow Valise connector body has one-piece nylon housing that assembles easily with two screws. Built-in cord grip has range of .22-.66 in. (5.6-16.8). IP20 suitability.	HBL52CM69V
Yellow Insulgr [®] plug with anchor locking screw to prevent accidental pull-out. The plug is "locked" into the receptacle when the screw is turned down so the head is flush with the plug surface. The cord grip range is .30-.69 in. (7.5-17.4). UL Recognized Component. IP20 suitability.	HBL52CM80C
Compact gray nylon panel mount inlet ideal for bass boat battery charging connection. Has gasketed spring-loaded lift cover for weatherproofing front and neoprene boot for weatherproofing rear. Will accept both 15A 125V and 20A 125V, 2 pole 3 wire straight blade connector bodies. IP44 suitability.	HBL61CM64
Same as HBL61CM64 except black in color.	HBL61CM64BK

Note: See page Tech-10 for Weather Resistant description.

Accessories

Description	Catalog Number
Yellow Seal-Tite [®] cover for weatherproofing straight blade Insulgr [®] plugs, HBL52CM66C and HBL53CM66C, when used with receptacles and connector bodies. Can also be used to weatherproof Insulgr [®] connector bodies when mating with flanged inlets. IP44 suitability. Note: For Insulgr [®] devices only.	HBL60CM17*
Yellow Seal-Tite cover for weatherproofing straight blade Insulgr [®] connector bodies, HBL52CM69C and HBL53CM69C, on extension cords and adapters. IP55 suitability. Note: For Insulgr [®] devices only.	HBL60CM18*
Yellow Valox [®] spring-loaded lift cover for weatherproofing duplex receptacles. Stainless steel screws and neoprene gasket included for mounting to FS/FD type weatherproof boxes. IP20 suitability.	HBL52CM21
Same as HBL52CM21 except gray in color.	HBL5221
Same as HBL52CM21 except for mounting to standard boxes.	HBL52CM22
Same as HBL52CM22 except gray in color.	HBL5222
Yellow Valox spring-loaded lift cover for weatherproofing single straight blade receptacles. Stainless steel screws and neoprene gasket included. For mounting to FS/FD type weatherproof boxes. IP44 suitability.	HBL74CM23WO
Same as HBL74CM23WO except gray in color.	HBL7423WO

Note: *Not UL Listed or CSA Certified.



HBL52CM62 HBL52CM61



HBL52CM66C



HBL52CM69C



HBL52CM80C



HBL52CM66V



HBL52CM69V



HBL61CM64

Dimensions in Inches (mm)



HBL60CM17



HBL60CM18
HBL60CM19



HBL52CM21



HBL74CM23WO

Rynite[®] is a registered trademark of E. I. DuPont.

Valox[®] is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.