
20 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC, 4 Pole, 4 Wire, Non-Grounding

Fed. Spec.


IP20 SUITABILITY



Plugs

Description	Cord Dia.	20A 3ØY 120/208V AC NEMA L18-20P 2 HP	20A 277/480V AC NEMA L19-20P 5 HP	20A 347/600V AC NEMA L20-20P
		Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2441	HBL2451	HBL2461

Note: See page C-53 for accessories.




HBL2441

Flanged Inlets

Description	Catalog Number		
Nylon casing, back wired.	HBL2445	HBL2455	HBL2465

Note: See page C-52 for accessories.



HBL2445

IP20 SUITABILITY



Connector Bodies

Description	Cord Dia.	20A 3ØY 120/208V AC NEMA L18-20R 2 HP	20A 277/480V AC NEMA L19-20R 5 HP	20A 347/600V AC NEMA L20-20R
		Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2443	HBL2453	HBL2463

Note: See pages C-52 and C-53 for accessories.




HBL2443

Single Flush Receptacles

Description	Catalog Number		
Black nylon face, back and side wired.	HBL2440	HBL2450	HBL2460

Note: See page C-52 for accessories.




HBL2440

Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	HBL2446	HBL2456	HBL2466

Note: See page C-52 for accessories.
See page C-69 for technical information.
See page C-45 for switched enclosure.
See page C-49 for Add-A-Shroud® kit. For use with connector bodies.
Only receptacles and plugs up to 480V AC are HP rated.
HP ratings are AC only.



HBL2446

Dimensions in Inches (mm)