

# Kellems® Wire Management Products

## Features and Benefits

### PolyTuff® I and PolyTuff® II Non-Metallic Liquidtight Conduit

All non-metallic construction ends fatigue and separation problems. They can be cut cleanly with a knife or PVC cutter so there are no jagged metal edges.



#### PolyTuff® I Conduit, Gray

- Rigid PVC core bonded to flexible PVC jacket
- Approved for outdoor use and direct burial
- UL Listed and CSA Certified



#### PolyTuff® II Tubing, Black

- PVC core with corrugated walls bonded to PVC jacket
- Handles twists, turns, bends, switchbacks and straightaways with ease
- UL Recognized and CSA Certified

### PolyTuff® I Conduit

**IP66**  
SUITABILITY



Trade Size (metric designator)	Feet (m)	Catalog Number
3/8 (12)	100 (30.5)	<b>G1038</b>
1/2 (16)	100 (30.5)	<b>G1050</b>
3/4 (21)	100 (30.5)	<b>G1075</b>
1 (27)	100 (30.5)	<b>G1100</b>
1 1/4 (35)	100 (30.5)	<b>G1125</b>
1 1/2 (41)	50 (15.2)	<b>G1150</b>
2 (53)	50 (15.2)	<b>G1200</b>

Note: See pages X-58 and X-59, X-90 and X-91 for approved fittings.  
See pages X-92 and X-93 for technical information and dimensional drawings.



### PolyTuff® II Tubing

**IP66**  
SUITABILITY



Trade Size (metric designator)	Feet (m)	Catalog Number
1/4 (10)	100 (30.5)	<b>B2025</b>
3/8 (12)	100 (30.5)	<b>B2038</b>
1/2 (16)	100 (30.5)	<b>B2050</b>
3/4 (21)	100 (30.5)	<b>B2075</b>
1 (27)	100 (30.5)	<b>B2100</b>
1 1/4 (35)	100 (30.5)	<b>B2125</b>
1 1/2 (41)	50 (15.2)	<b>B2150</b>
2 (53)	50 (15.2)	<b>B2200</b>

Note: See page X-90 for approved fittings.  
See pages X-92 and X-93 for technical information and dimensional drawings.

