## **Floor Boxes**





## Flush Round Single or Multi-Service Non-Metallic Floor Boxes, for Use In Concrete Floors

## **Dimensions Inches (mm)**

D		Description	Catalog Number	
		Adapter Required for all applications.	PFBA1A	
BCC	PFB1	Low Voltage Divider Required for use with catalog number PFB1 when used in multi-service applications. Accepts Hubbell standard duplex	PFBT1A	
Min. Depth of Pour	3.00" (76.2)	receptacles or 15A Twist-Lock <sup>®</sup> duplex		
Capacity	100 cubic inches prior to cutting level to floor (19.5 cubic inches per inch of depth).	receptacles (HBL4700 series). 	PFBYA1	
Dimensions – A	6.00" (152.4)	<sup>3</sup> / <sub>4</sub> in. "Y" adapter to feed parallel		
Dimensions – B	7.08" (179.8)	runs of ¾ in. conduit.		
Dimensions – C	6.69" (169.9)			
Dimensions – D	5.38" (136.5)	Pre-pour PVC stand increases <b>PFB1</b>	PFBSTAND	
Hubs	(2) 1.0" and (2) ¾" conduit hubs	box height 2.5 in. to 4.0 in. within		
Concrete Cover Included	✓	the concrete pour.	TL –	
Closure/Reducer Plugs	<ul> <li>(2) 1" plugs close off 1" hubs or reduce 1" to ¾"</li> <li>(2) ¾" plugs close off ¾" hubs or reduce ¾" to ½"</li> </ul>	-		

Note: UL File Number E92074. CSA File Number LR18416.

## Flush Round Covers and Flanges

Aulti-Service Cover and Tange Assemblies		SF39253A	PFBCBRA	PFBCBLA	PFBCGYA	PFBCIA	
ncludes floor box luplex flaps, (2) ½ oltage feed throu and matching carr 0.25 in. Diameter	cover with in. dia. low gh holes	8			m	•Ba	
	-	Brass	Brown Non-Metallic	Black Non-Metallic	Gray Non-Metallic	lvory Non-Metallic	
Single Service							I
Brass Aluminum	S3925 SA3925	S3725 SA3725	S2525 SA2525	S2725 SA2725	S2925 SA2925	S3525 —	S3325 —
3.88 in. Dia.	S	. 3	Ó	Ó			
	Duplex Flap	Duplex Screw	21/8" x 3/4" Combination	21/8" x 1" Combination	21/8" Single Receptacle	2%" Single Receptacle	21⁄8" Single Receptacle (Terrazzo Floor
Metal Carpet Flange		Adapter Ring			Furniture Feed Plate		
Use with single service covers for carpet applications. 6.25 in. Diameter		Use with single service covers for tile applications.			Unpainted plate with 1 in. threaded opening.		
S3082	SA3082		S5016	SA5016		PFBP1	
$\bigcirc$	0		$\bigcirc$	$\bigcirc$			
Brass	Brushed Aluminu	ım	Brass	Aluminum		Steel	
One Piece Bra	ass Cover and	Carpet Flang	je				
Brass Aluminum		SF3925 SFA3925	SF2525 —	SF2725 —	SF2925 —		
6.25 in. Dia.		and the second	1 and				
Note: Adapter ring St mounting SF series c	5016 is required for covers onto PFBA1A.	(E)			$( \bigcirc )$		
		Duplex Flap	2 <sup>1</sup> ⁄8" x <sup>3</sup> ⁄4" Combination	21/8" x 1"	21/8" Single		
			COMONAHON	Combination	Receptacle		