

Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages W-61 through W-68.

Straight Female Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)	Form Size	Catalog Number
1/2	.375"-.500"	F2	07401043
	.500"-.625"		07401045
3/4	.500"-.625"	F2	07401052
3/4	.625"-.750"	F4	07401053

90° Male Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)	Form Size	Catalog Number
3/8	.250"-.312"	F1	07401071
	.312"-.375"		07401072
	.375"-.437"		07401073
1/2	.187"-.250"	F2	07401074
	.250"-.375"		07401076
	.375"-.500"		07401078
	.500"-.625"		07401080*
3/4	.375"-.500"	F3	07401081
	.500"-.625"		07401083
	.625"-.750"		07401084*
	.750"-.875"		074011275*
1	.500"-.625"	F4	07401085
	.625"-.750"		07401087
	.750"-.875"		07401089
	.875"-.1.000"		07401091*
1 1/4	1.000"-.1.125"	F5	074011229*
	.750"-.875"		074011230
	.875"-.1.000"		07401137
	1.000"-.1.125"		07401108
1 1/2	1.125"-.1.250"	F5	074011042*
	1.250"-.1.375"		074011043
	1.000"-.1.125"		074011045
	1.125"-.1.250"		074011046
2	1.250"-.1.375"	F6	074011047
	1.312"-.1.437"		074011233
	1.437"-.1.562"		074011244
	1.562"-.1.687"		074011245
	1.687"-.1.812"		074011246
	1.750"-.1.875"		074011234*

45° Male Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)	Form Size	Catalog Number
1/2	.250"-.375"	F2	074011236
	.375"-.500"		074011021
	.500"-.625"		074011237*
3/4	.500"-.625"	F3	074011049
	.625"-.750"		074011051*
	.750"-.875"		074011239*
1	.625"-.750"	F4	074011055
	.750"-.875"		074011057
	.875"-.1.000"		074011199*
1 1/4	1.000"-.1.125"	F5	074011059
	1.125"-.1.250"		074011060

Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).

*Cable jacket may have to be stripped to pass through connector body.

Dimensions in Inches (mm)