

## Strain Relief for Liquidtight Conduit

Steel Fitting, Stainless Steel Mesh for Liquidtight Metal Conduit and PolyTuff® I Non-Metallic Conduit.

### IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages W-61 through W-68.



### Straight With Chase Fitting

Conduit Trade Size Inches	NPT Fitting Size Inches	Mesh Length Inches (cm)	Catalog Number
½	½	3.5" (8.89)	<b>07406079</b>
¾	¾	4" (10.16)	<b>07406080</b>
1	1	5" (12.70)	<b>07406081</b>
1¼	1¼	6" (15.24)	<b>07406082</b>
1½	1½	6.75" (17.14)	<b>07406083</b>



### 45° Angle With Male Fitting

Conduit Trade Size Inches	NPT Fitting Size Inches	Mesh Length Inches (cm)	Catalog Number (Insulated)
⅜	½	3" (7.62)	<b>074093561</b>
½	½	3.5" (8.89)	<b>074093562</b>
¾	¾	4" (10.16)	<b>074093563</b>
1	1	5" (12.70)	<b>074093564</b>
1¼	1¼	6" (15.24)	<b>074093565</b>
1½	1½	6.75" (17.14)	<b>074093566</b>
2	2	8" (20.32)	<b>074093568</b>

Note: For use with Liquidtight Metal conduit and PolyTuff® I Non-Metallic conduit.