

HOFFMAN ENCLOSURES, INC. 2100 Hoffman Way Minneapolis, MN 55303-1745, USA +1.763.421.2240 main

## **Declaration of Conformity**

Issued by Manufacturer Hoffman Enclosures, Inc. 2100 Hoffman Way, Anoka, Minnesota 55303-1745, U.S.A. declare at our sole responsibility, that these devices are designed and constructed according to the fundamental safety and health requirements.

Enclosure Models:	A**D**** (Bulletin A9)

Equipment Description: Hoffman NEMA Type 9

Enclosure Rating : CSA Class II, Groups E, F, and G

Enclosure Certification: CSA C22.2 No. 0-M1991

PRODUCTS CLASS 4418 02 - OUTLET BOXES AND FITTINGS - Boxes - For Hazardous Locations

Class II, Groups E, F and G

Enclosures, fabricated steel, Cat Nos. A-8D64, -8D84, -10D84, -10D106, -12D106, -12D126, -12D128, -16D126, -16D128, -16D126, -20D168, -20D208, -24D208, -24D2410, -30D2410, -36D2410, -36D3012, -48D3612, threaded for conduit connection or field drilling and tapping, conduit sizes 1/2 in through 2 in.

**Applicable Standards:** 

CSA C22.2 No. 0-M1991 – General Requirements – Canadian Electrical Code, Part II CSA C22.2 No. 0.4-M1982 – Bonding and Grounding of Electrical Equipment CSA C22.2 No. 0.5-M1982 – Threaded Conduit Entries CSA C22.2 No. 25-1966 – Enclosures for Use in Class II, Groups E, F & G Hazardous Locations

Authorized by:

Glin Kampa

Glen Kampa

<u>5/22/2020</u> (today's date)

Date

**Senior Regulatory Engineer** 

DOC: CERT-00242-A

Subject to Change Without Notice



## **Certificate of Compliance**

Certificate:	1675743	
Project:	1675743	
Issued to:	Hoffman Enclosures Inc.	
	2100 Hoffman Way Anoka, MN 55303-1745	

USA

Attention: Tom Hurney

Master Contract:	151630
Date Issued:	2005/06/03

The products listed below are eligible to bear the CSA Mark shown



Issued by: E

Ezio Migliozi

Authorized by: Nick Alfano, Operations Manager

PRODUCTS CLASS 4418 02 - OUTLET BOXES AND FITTINGS - Boxes - For Hazardous Locations

Class II, Groups E, F and G

Enclosures, fabricated steel, Cat Nos. A-8D64, -8D84, -10D84, -10D106, -12D106, -12D126, -12D128, -16D126, -16D128, -16D126, -20D168, -20D208, -24D208, -24D2410, -30D2410, -36D2410, -36D3012, -48D3612, threaded for conduit connection or field drilling and tapping, conduit sizes 1/2 in through 2 in.

## APPLICABLE REQUIREMENTS

CSA C22.2 No. 0-M1991 - General Requirements - Canadian Electrical Code, Part II

CSA C22.2 No. 0.4-M1982 - Bonding and Grouding of Electrical Equipment



Certificate:	1675743	Master Contract:	151630
Project:	1675743	Date Issued:	2005/06/03

CSA C22.2 No. 0.5-M1982 - Threaded Conduit Entries

CSA C22.2 No. 25-1966 -Enclosures for Use in Class II, Groups E, F and G Hazardous Locations.