

## Metallic Four-Way 15° Angle Back Box

### Ordering Information

| Description   | UPC          | Catalog Number |
|---|--------------|----------------|
| Metallic Back Box, Pin and Sleeve Insulgrip, Feed Through | 783585011325 | MB601007W      |

**Product Type**  
Accessories

### Standards

UL Listed  
CSA Certified

### Specifications

|                 |                 |
|-----------------|-----------------|
| Gaskets         | Neoprene        |
| Hinge Spring    | Stainless Steel |
| Assembly Screws | Stainless Steel |
| Box Hub Size    | 1 1/2" NPT      |

### Performance

| Electrical              |  |
|-------------------------|--|
| Current Interrupting    | Certified for current interrupting at full rated current   |
| Dielectric Voltage      | Withstands 3,000V AC   |
| Max Working Voltage     | 600V AC RMS  |
| Mechanical              |  |
| Impact Resistance       | In accordance with UL746C  |
| Product Identification  | Identification and ratings are a part of the external label and molded into the receptacle mount |
| Terminal Identification | Terminals identified in accordance with North American and International conventions             |
| Environmental           |  |
| Flammability            | UL94-5VA and V-0 classification  |
| Operating Temperatures  | Max. Continuous: 75° C; Min. Continuous: -40° C w/o impact                                       |

### Online Resources

Customer Use Drawing  
eCatalog  
Installation Instructions

