

## Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

### IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages W-61 through W-68.

### Straight Female Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)		Form Size	Catalog Number
½	.375"-.500"	(.95-1.27)	F2	<b>07401043</b>
	.500"-.625"	(1.27-1.59)		<b>07401045</b>
¾	.500"-.625"	(1.27-1.59)	F2	<b>07401052</b>
¾	.625"-.750"	(1.59-1.90)	F4	<b>07401053</b>

### 90° Male Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)		Form Size	Catalog Number
¾	.250"-.312"	(.63-.79)	F1	<b>07401071</b>
	.312"-.375"	(.79-.95)		<b>07401072</b>
	.375"-.437"	(.95-1.11)		<b>07401073</b>
½	.187"-.250"	(.47-.63)	F2	<b>07401074</b>
	.250"-.375"	(.63-.95)		<b>07401076</b>
	.375"-.500"	(.95-1.27)		<b>07401078</b>
¾	.500"-.625"	(1.27-1.59)	F3	<b>07401080*</b>
	.375"-.500"	(.95-1.27)		<b>07401081</b>
	.500"-.625"	(1.27-1.59)		<b>07401083</b>
	.625"-.750"	(1.59-1.90)		<b>07401084*</b>
1	.750"-.875"	(1.90-2.22)	F4	<b>074011275*</b>
	.750"-.875"	(1.90-2.22)		<b>07401085</b>
	.875"-1.000"	(2.22-2.54)		<b>07401087</b>
	1.000"-1.125"	(2.54-2.86)		<b>07401089</b>
1¼	.750"-.875"	(1.90-2.22)	F5	<b>07401091*</b>
	.875"-1.000"	(2.22-2.54)		<b>074011229*</b>
	1.000"-1.125"	(2.54-2.86)		<b>074011230</b>
	1.125"-1.250"	(2.86-3.17)		<b>07401137</b>
1½	1.125"-1.250"	(2.86-3.17)	F5	<b>07401108</b>
	1.250"-1.375"	(3.18-3.51)		<b>074011042*</b>
	1.000"-1.125"	(2.54-2.86)		<b>074011043</b>
	1.125"-1.250"	(2.86-3.17)		<b>074011045</b>
2	1.250"-1.375"	(3.17-3.49)	F6	<b>074011046</b>
	1.312"-1.437"	(3.33-3.65)		<b>074011047</b>
	1.437"-1.562"	(3.65-3.97)		<b>074011233</b>
	1.562"-1.687"	(3.96-4.29)		<b>074011244</b>
2	1.687"-1.812"	(4.28-4.60)	F6	<b>074011245</b>
	1.750"-1.875"	(4.44-4.76)		<b>074011246</b>
	1.750"-1.875"	(4.44-4.76)		<b>074011234*</b>

### 45° Male Thread

NPT Thread Size Inches	Grip Diameter Range Inches (cm)		Form Size	Catalog Number
½	.250"-.375"	(.63-.95)	F2	<b>074011236</b>
	.375"-.500"	(.95-1.27)		<b>074011021</b>
	.500"-.625"	(1.27-1.59)		<b>074011237*</b>
¾	.500"-.625"	(1.27-1.59)	F3	<b>074011049</b>
	.625"-.750"	(1.59-1.90)		<b>074011051*</b>
	.750"-.875"	(1.90-2.22)		<b>074011239*</b>
1	.625"-.750"	(1.59-1.90)	F4	<b>074011055</b>
	.750"-.875"	(1.90-2.22)		<b>074011057</b>
	.875"-1.000"	(2.22-2.54)		<b>074011199*</b>
1¼	1.000"-1.125"	(2.54-2.86)	F5	<b>074011059</b>
	1.125"-1.250"	(2.86-3.17)		<b>074011060</b>

Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).

\*Cable jacket may have to be stripped to pass through connector body.

Dimensions in Inches (mm)