






**PB2 BaseTrak**













Description	Color	Length	Catalog Number	Description	Color	Length	Catalog Number
<b>Base</b> Two channel raceway. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths.  Assembled cover and base dimensions. W: 4.50" (114.30) H: 1.63" (41.40) 	Office White	5 ft. 10 ft.	<b>PB2B5</b> <b>PB2B10</b> A: 1.42" (36.07) B: 4.50" (114.30)	<b>Cover</b> Cover allows access to multiple channels. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths. 	Office White	5 ft. 10 ft.	<b>PB2C5</b> <b>PB2C10</b> B: 4.50" (114.30)
				<b>Split Cover</b> Cover allows separation of channels and access to a single channel. Available in 5 ft. (1.5m) and 10 ft. (3m) lengths. Two split covers are required for each raceway section. 	Office White	5 ft. 10 ft.	<b>PB2SPL5</b> <b>PB2SPL10</b> B: 2.22" (56.39)

Note: Available in PRE-WIRED.

**Device Boxes**

Description	Color	Catalog Number
<b>2-Gang In-Line Box</b> For switches, receptacles and communication devices. Provides flush look. See page U-62 for recommended single gang "KP" plate options. 	Office White	<b>PB2IND2G</b> A: 7.66" (194.56) B: 4.74" (120.40) C: 1.84" (46.74)

**Fittings**

Description	Color	Catalog Number	Description	Color	Catalog Number
<b>Internal Elbow, Base and Cover</b> Full capacity 1-1/4 in. bend radius internal elbow. 	Office White	<b>PB3IEBCA</b> A: 4.36" (110.74) B: 4.72" (119.89) C: 4.36" (110.74)	<b>External Elbow, Base and Cover</b> Full capacity 1-1/4 in. bend radius external elbow. 	Office White	<b>PB3EEBCA</b> A: 6.48" (164.59) B: 4.72" (119.89) C: 6.48" (164.59)
<b>Flat Elbow, Base and Cover</b> Full capacity 1-1/4 in. bend radius flat elbow. 	Office White	<b>PB3FEBCA</b> A: 7.64" (194.66) B: 7.64" (194.66) C: 1.71" (43.43)	<b>Tee, Base and Cover</b> Full capacity 1-1/4 in. bend radius tee. 	Office White	<b>PB3TCBCA</b> A: 7.37" (187.20) B: 7.08" (179.83) C: 2.72" (69.09)
<b>Splice Cover</b> For covering potential openings where two lengths of raceway come together. 	Office White	<b>PB3SC</b> A: 1.56" (39.62) B: 4.74" (120.40) C: 1.69" (42.93)	<b>Safety Strap</b> For preventing potential tampering with PB2 BaseTrak cover. Can also be used as a splice cover. 	Office White	<b>PB3SS</b> A: 1.50" (38.10) B: 6.01" (152.65) C: 1.74" (44.20)
<b>Conduit Adapter/Ceiling Fitting</b> For connecting conduit to raceway. Also use for ceiling feeds. Has combination 1/2 in., 3/4 in., 1 in., 1-1/4 in. and 1 1/2 in. trade size KOs. 	Office White	<b>PB2CACF</b> A: 4.72" (119.89) B: 5.22" (132.70) C: 6.30" (160.02)	<b>Reducer</b> Reduces from PB2 BaseTrak Raceway to PW2 WallTrak® Raceway. 	Office White	<b>PB3REDA</b> A: 3.50" (88.90) B: 4.72" (119.89) C: 1.73" (43.94)
<b>Transition Fitting</b> Transitions horizontal PB2 BaseTrak to vertical PW2 WallTrak, PL1 LANTrak® or PP1 PremiseTrak®. 	Office White	<b>PB3TRBC</b> A: 3.22" (81.79) B: 7.28" (184.91) C: 2.42" (61.47)	<b>Surface Panel Connector</b> For connecting PB2 Raceway with surface type panel boxes. 	Office White	<b>PB3SPCA</b> A: 2.22" (56.39) B: 5.66" (143.76) C: 1.60" (40.64)
<b>Wire Clip</b> For holding conductors in place. 	Office White	<b>PB2WC</b> A: 1.29" (50.20) B: 1.00" (25.40)	<b>End Cap</b> For closing end of PB2 BaseTrak® Raceway. 	Office White	<b>PB3ECA</b> A: 2.02" (51.31) B: 4.68" (118.97) C: 1.72" (43.69)

Dimensions in Inches (mm)