


15 Amp 2 and 3 Wire Devices



Wallplates, 1-Gang

Description	Color	Duplex Receptacles	Single Receptacles with Face Dia. 1.40" (35.6)
Nylon, smooth.	Brown Ivory	P8 P8I	P7 P7I
Stainless steel 302/304, .035 in. (0.9), horizontal brushed finish.		SS8	SS7
Stainless steel 430, .035 in. (0.9), horizontal brushed finish.		SS8L	SS7L
Brass .04 in. (1.0), horizontal brushed finish.		SB8	SB7
Aluminum .05 in. (1.3), horizontal brushed finish.		SA8	SA7



P8

SS7

Weatherproof Covers

IP44
SUITABILITY

Description	Duplex Receptacles	Single Receptacles with Face Dia. 1.40" (35.6)
Cast aluminum, for standard horizontal box mount.	HBL5205WO	—
Same as above except FS/FD box mount.	HBL5206WO	—
Cast aluminum vertical FS/FD box mount.	—	HBL7420
Gray thermoplastic, vertical standard box mount, corrosion resistant.	HBL5222	—
Same as above except yellow.	HBL52CM22	—
Gray thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL5221	HBL7423WO
Yellow thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21	HBL74CM23WO
White thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21W	—



HBL5206WO



HBL5221



HBL7423WO



WP1

Weatherproof Covers for
15A Nylon Flanged Receptacles and InletsIP44
SUITABILITY

Description	Duplex Receptacles	Single Receptacles with Face Dia. 1.40" (35.6)
Gray thermoplastic, corrosion resistant.	—	WP1

Note: All weatherproof covers listed above are UL Listed for wet and damp locations with cover closed.
Those with suffix WO are UL Listed with cover open.
See page O-21 for additional information on weatherproof covers.

Dimensions in Inches (mm)