

Product availability : Stock - Normally stocked in distribution facility



Price\* : 182.00 USD



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	100 VA
Primary voltage	277 V
Secondary voltage	120 V
Range of product	T

### Complementary

Phase	1 phase
Rated power in VA	100 VA
Primary voltage	277 V : 120 V
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Height	2.89 in
Width	3.38 in
Depth	3.34 in
Material	Copper winding
Product compatibility	FSC1

### Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239 CE
NEMA degree of protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

### Ordering and shipping details

Category	16200 - 9070 T (NOT TF) 50-200VA
----------	----------------------------------

Discount Schedule	CP8
GTIN	00785901905776
Nbr. of units in pkg.	1
Package weight(Lbs)	3.8500000000000001
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	10 years
-----------------	----------