


Midget Plugs and Flanged Inlets




HBL7465V




HBL7594V




HBL7594




HBL7570




HBL7466, HBL7467




HBL7595N



HBL7595



HBL7486N



HBL7486

IP20
SUITABILITY



**15A 125V
NEMA ML-1P**

**15A 125V
NEMA ML-2P**

**15A 125/250V AC
NEMA ML-3P**

Plugs

Description	Cord Dia.	Catalog Number		
Valise® plug, black nylon, multiple drive screw terminals.	.220"-.385" (5.6-9.8)	HBL7465V*	—	—
Valise® plug, black nylon, insulation displacement terminals.	.300"-.430" (7.6-10.9)	—	HBL7594V	—
Black nylon cover, phenolic body, multiple drive screw terminals.	.281"-.421" (7.1-10.7)	—	HBL7594	—
Angle plug, black nylon cover, phenolic body, multiple drive screw terminals.	.335"-.421" (8.5-10.7)	—	HBL7570	—
Valise® plug, black nylon, with insulation displacement terminals.	.300"-.430" (7.6-10.9)	—	—	HBL7485V*
Black nylon body, phenolic base, multiple drive screw terminals, cord grip.	.281"-.421" (7.1-10.7)	—	—	HBL7485*
Same as above, except angle cord grip.	.335"-.421" (8.5-10.7)	—	—	HBL7432*

Flanged Inlets

Description	Catalog Number		
Stainless steel flange, polarized, exposed terminals.	HBL7467*	—	—
Stainless steel flange, not polarized, exposed terminals.	HBL7466*	—	—
Exposed terminals, black nylon flange.	—	HBL7595N	—
Exposed terminals, stainless steel flange.	—	HBL7595	—
Covered terminals, stainless steel flange, accepts cord .500" (12.7) dia.	—	HBL7551	—
Exposed terminals, black nylon flange.	—	—	HBL7486N*
Exposed terminals, stainless steel flange.	—	—	HBL7486*

Note: See page B-8 for accessories.

*UL Listed only.

Male ML-2P devices have hollow center ground sleeves.

Male ML-3P devices have solid center neutral pins.

Dimensions in Inches (mm)