

## 15 Amp 2 and 3 Wire Devices

### Pool Kit Contains:

- Heavy duty, industrial grade locking receptacle NEMA L5-20, 20A 125V
- Single-pole switch (20A, 120-277V AC)
- Two gang, 2 inch deep die-cast aluminum weatherproof box with (4) 3/4 inch threaded outlets
- Two gang, weatherproof while-in-use cover
- Includes mounting hardware, gasket, wire connector and (3) closure plugs
- Complete assembly instructions

Tinted lid is aesthetically pleasing in any location. High-impact, polycarbonate while-in-use cover will not rust or corrode; cover is NEMA 3R rated

Compact 2-gang design



### Pool Pump Kit



Description	Catalog Number
Pool pump receptacle kit.	HBLPKL520

Note: See Section L for additional information on SWITCHOUT Lockout devices.

### Weatherproof, Seal-Tite®, Triple Seal Boots for 15A Insulgrip® Devices

IP55\*  
SUITABILITY

Description	For 3 Wire Devices	For 3 Wire EdgeConnect™ Devices
Black elastomer boot for plugs when used in a cord set and connector bodies when used with a flange inlet.	HBL6023	HBL6023ST
Same as above except yellow elastomer.	HBL60CM23	HBL60CM23ST
Black elastomer boot for connector bodies when used in cord sets.	HBL6024	HBL6024ST
Same as above except yellow elastomer.	HBL60CM24	HBL60CM24ST

Note: \*When installed and used properly with plug and connector body combinations.

### PLUGOUT® Lockout Devices

Description	Catalog Number
Lockout device for 15A and 20A straight blade, and 15A Twist-Lock plugs.	HLDMP
Lockout device for attachable 20A and 30A Twist-Lock plugs, straight body or angle types, with or without weatherproof covers.	HLD
Lockout device for 15A and 20A, 125V straight blade plugs with holes in blades.	HKLDR

Note: See Section L for additional information on PLUGOUT® lockout devices.

### Nylon Convenience Adapters



NEMA Configuration							
Catalog Number	HBL2270	HBL2271	HBL2128	HBL2274	HBL2129	HBL31CM28	HBL31CM29*
Male Blade End							
Female Slot End							

Note: \*Not UL Listed.

Caution: Where adapters have different ratings on the blade and slot end the following precautions must be exercised in their use. (1) Remember that overcurrent protection is determined by the blade end.

(2) The use of the adapter should be limited to the lowest rated end of the adapter in order to prevent overheating. (3) Adapters do not provide GFCI, overcurrent or short circuit protection.

### Plug In Adapters



Description	Catalog Number
Male end - 2 wire parallel polarized blades, 15A, 125V. Female end - 3 wire 15A, 125V straight slot grounding.	HBL5273L
Male end - 3 wire crow foot 15A, 125V blades. Female end - 3 wire 15A, 125V straight slot grounding.	HBL5289**
Male end - 3 wire 10A, 250V, 15A, 125V Twist-Lock blades. Female end - 3 wire 15A, 125V straight slot grounding.	9053A**
Male end - 3 wire 15A, 125V straight blade grounding. Female end - 10A, 250V, 15A 125V Twist-Lock slots.	9054A**

Note: \*\*Must always be used with a grounded receptacle.

\*Not UL Listed.

Dimensions in Inches (mm)