

20 Amp, 125, 250 Volts and 277 Volts AC 2 Pole, 3 Wire, Grounding


**20A 125V
NEMA L5-20R
1 HP**
**20A 250V
NEMA L6-20R
2 HP**
**20A 277V AC
NEMA L7-20R
2 HP**



HBL2323SW




HBL2313




HBL2313ST




HBL2313VY



HBL2320SW



HBL2310ST



HBL2320SR

Dimensions in Inches (mm)

Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4X, 12

Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox clamps.	.360"-.930" (9-24)	HBL2313SW	HBL2323SW	HBL2333SW

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.360"-.930" (9-24)	HBL2313	HBL2323	HBL2333
Black and white nylon, spring termination.	.360"-.930" (9-24)	HBL2313ST	HBL2323ST	HBL2333ST
Spring termination, all black.	.360"-.930" (9-24)	HBL2313STBK	HBL2323STBK	—
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	HBL23CM13	HBL23CM23	—
All black nylon.	.360"-.930" (9-24)	HBL2313BK	HBL2323BK	—
Cord clamps with removable inserts. All black nylon.	.360"-.930" (9-24)	HBL2313EBK	HBL2323EBK	—

Note: See pages C-52 and C-53 for accessories.



Valise®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Yellow nylon.	.325"-.720" (8.26-18.3)	HBL2313VY	HBL2323VY	—
Black nylon.	.325"-.720" (8.26-18.3)	HBL2313VBK	HBL2323VBK	HBL2333VBK

Note: See page C-53 for accessories.

Receptacles

Watertight Safety-Shroud

IP66 SUITABILITY

UL Type 4X, 12

Description	Catalog Number		
Gray Valox housing and flange, back wired.	HBL2310SW	HBL2320SW	HBL2330SW

Note: See page C-54 for accessories.

Safety-Shroud Twist-Lock

IP20 SUITABILITY

Description	Catalog Number		
Gray Valox angle housing, one gang, back wired.	HBL2310AR	HBL2320AR	HBL2330AR
Gray Valox surface mounting, one gang, back wired.	HBL2310SR	HBL2320SR	HBL2330SR
Gray Valox semi-flush, two gang, back wired.	HBL2310SR2	HBL2320SR2	HBL2330SR2

Single Flush Receptacles

IP20 SUITABILITY

Description	Catalog Number		
Black nylon face, back and side wired.	HBL2310	HBL2320	HBL2330
Black nylon face, spring terminals.	HBL2310ST	HBL2320ST	HBL2330ST
Blue nylon face, back and side wired.	HBL2310M7	HBL2320M4	—
Red nylon face, spring terminals.	HBL2310STR	HBL2320STR	—
Isolated ground, orange nylon face, back and side wired.	IG2310	IG2320	—
Isolated ground, orange nylon face, spring termination.	IG2310ST	—	—
Corrosion resistant, yellow nylon face, back and side wired.	HBL23CM10	—	—
Ring terminal connection.	HBL2310RT	HBL2320RT	—

Note: See page C-52 for accessories.

Insulgrip® Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	HBL2316	HBL2326	HBL2336
Nylon casing, back wire, spring termination.	HBL2316ST	HBL2326ST	—

Note: See page C-52 for accessories.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.