

# Product data sheet

## Characteristics

# 2510FG5P

FHP Manual Starter - NEMA 1 - 1P - Toggle w/  
Guard - Red Indicator - 277VAC

Product availability : Stock - Normally stocked in distribution facility



Price\* : 147.31 USD



### Main

Product or component type	Single Unit Manual Starter
Range of product	F
Thermal overload type	Melting alloy

### Complementary

Line Rated Current	16 A
Cable entry	0.5" and 0.75" knock-outs (top and bottom)
Motor power hp	1 hp at 115 V AC 1 hp at 230 V AC 1 hp at 277 V AC
System Voltage	277 V AC
Poles description	1P
Control type	Toggle switch (with lock-off)
Phase	1 phase
Local signalling	Red indicator
Reset	Manual
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
AWG gauge	AWG 14...AWG 12 (copper)
Height	4.25 in
Width	2.44 in
Depth	2.88 in

### Environment

Product certifications	CE UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05
------------------------	---

NEMA degree of protection	NEMA 1 plastic standard size
---------------------------	------------------------------

**Ordering and shipping details**

Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901554028
Nbr. of units in pkg.	3
Package weight(Lbs)	0.8399999999999997
Returnability	Y
Country of origin	MX

**Offer Sustainability**

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

**Contractual warranty**

Warranty period	18 months
-----------------	-----------