

# 2510FW1

## FHP Manual Starter - NEMA 4 - 1 Conduit Opening - 1P - No Indicator - 277VAC

Product availability : Stock - Normally stocked in distribution facility



Price\* : 323.20 USD



### Main

Product or component type	Single Unit Manual Starter
Range of product	F
Thermal overload type	Melting alloy

### Complementary

Line Rated Current	16 A
Cable entry	0.75 NPT (bottom)
Motor power hp	1 hp at 115 V AC 1 hp at 230 V AC 1 hp at 277 V AC
System Voltage	277 V AC
Poles description	1P
Control type	Toggle switch (with lock-off)
Phase	1 phase
Local signalling	No indicator
Reset	Manual
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
AWG gauge	AWG 14...AWG 12 (copper)
Height	4.38 in
Width	3 in
Depth	4.25 in

### Environment

Product certifications	CE UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05
------------------------	---

NEMA degree of protection	NEMA 4 die cast zinc alloy standard size
---------------------------	--

## Ordering and shipping details

Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901554332
Nbr. of units in pkg.	1
Package weight(Lbs)	2.8999999999999999
Returnability	Y
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

## Contractual warranty

Warranty period	18 months
-----------------	-----------