

## 30A Twist-Lock Devices

**30 Amp, 3ØY 120/208,  
277/480 and 347/600  
Volts AC, 4 Pole,  
5 Wire, Grounding**

**Plugs****Watertight Safety-Shroud®**

| Description                                  | Cord Dia.           | Catalog Number |         |           |           |
|----------------------------------------------|---------------------|----------------|---------|-----------|-----------|
| Black Valox® housing,<br>white Valox clamps. | .350"-1.150" (9-29) | HBL2811SW      | HBL2801 | HBL2821SW | HBL2831SW |

| Safety-Shroud®                                                                                          |                     | IP20 SUITABILITY |   |   |   |
|---------------------------------------------------------------------------------------------------------|---------------------|------------------|---|---|---|
| Description                                                                                             | Cord Dia.           | Catalog Number   |   |   |   |
| Black and white nylon body,<br>white Valox shroud. Can be used<br>with the Insulgrip® Connector Bodies. | .350"-1.150" (9-29) | HBL2811S         | — | — | — |

Note: See page C-48 for accessories.

**Insulgrip**

|                                               |                     | IP20 SUITABILITY |   |           |         |
|-----------------------------------------------|---------------------|------------------|---|-----------|---------|
| Description                                   | Cord Dia.           | Catalog Number   |   |           |         |
| Black and white nylon.                        | .350"-1.150" (9-29) | HBL2811          | — | HBL2821   | HBL2831 |
| Black and white nylon,<br>spring termination. | .350"-1.150" (9-29) | HBL2811ST        | — | HBL2821ST | —       |
| Corrosion resistant, yellow nylon.            | .350"-1.150" (9-29) | HBL28CM11        | — | —         | —       |
| Black and white for flat cable.               | .350"-1.150" (9-29) | HBL2811FC        | — | —         | —       |
| All black nylon.                              | .350"-1.150" (9-29) | HBL2811BK        | — | —         | —       |
| All black nylon, spring termination.          | .350"-1.150" (9-29) | HBL2811STBK      | — | —         | —       |

Note: See page C-53 for accessories.

**Flanged Inlets****Watertight Safety-Shroud**

| Description                     |  | Catalog Number |         |   |   |
|---------------------------------|--|----------------|---------|---|---|
| Gray Valox® housing and flange. |  | HBL2815SW      | HBL2805 | — | — |

Note: See page C-54 for accessories.

**Insulgrip®**

| Description                       |           | Catalog Number |           |         |
|-----------------------------------|-----------|----------------|-----------|---------|
| Nylon casing, back wired.         | HBL2815   | —              | HBL2825   | HBL2835 |
| Nylon casing, spring termination. | HBL2815ST | —              | HBL2825ST | —       |

Note: See page C-52 for accessories.

See pages C-69 and C-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.

**Twist-Lock® 3-Phase Circuit Tester**

| Description             | Rating                                 | Catalog Number |   |   |   |
|-------------------------|----------------------------------------|----------------|---|---|---|
| 3-phase circuit tester. | 3Ø 120/208V AC<br>Min. Voltage: 90V AC | HBL3PT2811     | — | — | — |

Note: Testers in other NEMA configurations can be developed upon request.  
See page C-52 for additional circuit testers.



**HBLMITL** - For use with  
Watertight Safety-Shroud  
receptacles, see page C-48.



HBL3PT2811

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)



**30A 3ØY  
120/208V  
AC NEMA  
L21-30P 3 HP**


**30A 3ØY  
240/415V  
AC NEMA  
L26-30P**

**30A 3ØY  
277/480V AC  
NEMA L22-  
30P 10 HP**

**30A 3ØY  
347/600V  
AC NEMA  
L23-30P**

IP66 SUITABILITY

UL Type 4X, 12



HBL2811SW




HBL2811S



HBL2811



HBL2815SW



HBL2815