

Twist-Lock® Devices
15A, 277V AC, 2 Pole, 3 Wire Grounding
Receptacle

HUBBELL

Features

- Reinforced thermoplastic construction
- Single piece, all brass contacts
- All terminals are back and side wired
- Brass mounting strap with stainless steel grounding clip

Ordering Information

Description	Device Color	UPC	Catalog Number
Single, black nylon face mounted on a 4" (101.6) round box cover	Black	783585236896	HBL4761

Listings

Listed to UL 498
Fed. Spec. W-C-596
Certified to CSA C22.2 No.42

Specifications


Face	RTP
Base	RTP
Contacts	Brass
Clamp	Brass
Ground Contact	Brass
Terminal Screws	Brass

Performance

Electrical	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum
Mechanical	
Terminal Accommodation	#18 AWG - #10 AWG solid or stranded copper wire only.
Terminal Identification	Terminals identified in accordance with UL 498
Environmental	
Flammability	HB or better per UL94/CSA 22.2 No.0.17
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (w/o impact)



15A 277V AC
NEMA L7-15R
UL/CSA
2 HP



Accessories

Plug	HBL4770C
------	----------

Resources

Customer Use Drawing
eCatalog

