50 Amp, 250 Volts DC and 600 Volts AC

IP20 SUITABILITY





Plugs

Description	Cord Dia.	Catalog Number	
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	HBL3765C	HBL7765C


Note: See page C-60 for accessories.



HBL3765C

Flanged Inlets

Description	Catalog Number	
Zinc plated steel casing, thermoset interior.	HBL3775	HBL7958
Zinc plated steel casing, thermoset interior with lift cover.	HBL3768	HBL7968



HBL3775

IP20 SUITABILITY






Connector Bodies

Description	Cord Dia.	Catalog Number	
Nylon cover, thermoplastic polyester interior.	.830"-1.250"(21.08-31.75)	HBL3764C	HBL7764C

Note: See page C-60 for accessories.




HBL3768


Receptacles

Description	Catalog Number	
Black phenolic.	HBL3769	HBL7379

Note: See page C-60 for accessories.



HBL3764C



HBL3769

Important Note: Catalog numbers HBL7765C, HBL7958, HBL7968, HBL7764C, HBL7379 are for replacement use only. See other singly rated 50A Twist-Lock® devices in this section. HBL3700 series Twist-Lock devices do not interchange with any other devices in this section.

Dimensions in Inches (mm)