

30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC 4 Pole, 4 Wire, Non-Grounding


IP20
SUITABILITY



30A 3ØY 120/208V AC
NEMA L18-30P
3 HP

30A 3ØY 277/480V AC
NEMA L19-30P
10 HP

30A 3ØY 347/600V AC
NEMA L20-30P



HBL2751

Plugs

| Description | Cord Dia. | Catalog Number |
|------------------------|------------------------|--|
| Black and white nylon. | .350"-1.150" (9-29) | HBL2751 HBL2761 HBL2771 |

Note: See page B-53 for accessories.

Flanged Inlets

| Description | Catalog Number |
|---------------------------|--|
| Nylon casing, back wired. | HBL2755 HBL2765 HBL2775 |

Note: See page B-52 for accessories.

IP20
SUITABILITY



30A 3ØY 120/208V AC
NEMA L18-30R
3 HP

30A 3ØY 277/480V AC
NEMA L19-30R
10 HP

30A 3ØY 347/600V AC
NEMA L20-30R

Connector Bodies

| Description | Cord Dia. | Catalog Number |
|------------------------|------------------------|--|
| Black and white nylon. | .350"-1.150" (9-29) | HBL2753 HBL2763 HBL2773 |

Note: See page B-52 for accessories.

Single Flush Receptacles

| Description | Catalog Number |
|--|--|
| Black nylon face, back and side wired. | HBL2750 HBL2760 HBL2770 |


Note: See page B-52 for accessories.

Flanged Receptacles

| Description | Catalog Number |
|---------------------------|--|
| Nylon casing, back wired. | HBL2756 HBL2766 HBL2776 |

Note: See page B-52 for accessories.


See page B-69 for technical information on Twist-Lock devices.




HBL2755



HBL2753



HBL2750



HBL2756

Dimensions in Inches (mm)