

**Form Size 1-4**

UL Listed to  
Type 4, 4X, 12 and 13

IP66\*  
SUITABILITY



**Straight Male**

NPT Hub Size	Cord Dia. Inches (mm)	Form Size	Color Code	Machined Aluminum	Machined Zinc-Plated Steel	Stainless Steel	Nylon Gray	Nylon Black
1/4	.06"- .13" (1.6-3.2)	F1	Green	—	—	—	SHC1001CR	—
	.13"- .19" (3.2-4.7)		Orange	SHC1002	—	—	SHC1002CR	—
	.19"- .25" (4.7-6.3)		Red	SHC1003	—	SHC1003SS	SHC1003CR	—
	.25"- .31" (6.3-7.9)		Black	SHC1004	—	SHC1004SS	SHC1004CR	—
	.31"- .38" (7.9-9.5)		White	SHC1005**	—	—	SHC1005CR	SHC2005CR
	.38"- .44" (9.5-11)		Blue	—	—	—	SHC1006CR	—
3/8	.06"- .13" (1.6-3.2)	F1	Green	SHC1007	—	—	—	—
	.13"- .19" (3.2-4.7)		Orange	SHC1008	SHC1008ZP	—	SHC1008CR	SHC2008CR
	.19"- .25" (4.7-6.3)		Red	SHC1009	—	SHC1009SS	SHC1009CR	—
	.25"- .31" (6.3-7.9)		Black	SHC1010	SHC1010ZP	—	SHC1010CR	SHC2010CR
	.31"- .38" (7.9-9.5)		White	SHC1011	—	SHC1011SS	SHC1011CR	SHC2011CR
	.38"- .44" (9.5-11.0)		Blue	SHC1012	SHC1012ZP	SHC1012SS	SHC1012CR	SHC2012CR
1/2	.19"- .25" (4.7-6.3)	F1	Red	SHC1015	—	—	—	—
	.25"- .31" (6.3-7.9)		Black	SHC1016	—	—	—	—
	.31"- .38" (7.9-9.5)		White	SHC1017	—	—	—	—
	.38"- .44" (9.5-11.0)		Blue	SHC1018	—	—	—	—
1/2	.06"- .13" (1.6-3.2)	F2	Green	SHC1019	—	—	SHC1019CR	—
	.13"- .19" (3.2-4.7)		Orange	SHC1020	SHC1020ZP	SHC1020SS	SHC1020CR	—
	.19"- .25" (4.7-6.3)		Red	SHC1021	SHC1021ZP	SHC1021SS	SHC1021CR	SHC2021CR
	.25"- .38" (6.3-9.7)		White	SHC1022	SHC1022ZP	SHC1022SS	SHC1022CR	SHC2022CR
	.38"- .50" (9.7-12.7)		Blue	SHC1023	SHC1023ZP	SHC1023SS	SHC1023CR	SHC2023CR
	.50"- .63" (12.7-15.9)		Brown	SHC1024	SHC1024ZP	SHC1024SS	SHC1024CR**	SHC2024CR**
1/2	.38"- .50" (9.7-12.7)	F3	Blue	SHC1025	—	—	—	—
	.50"- .63" (12.7-15.9)		Brown	SHC1026	—	—	—	—
	.63"- .75" (15.9-19.0)		Yellow	SHC1027**	SHC1027ZP**	—	—	—
	.75"- .88" (19.0-22.2)		Orchid	SHC1028**	SHC1028ZP**	—	—	—
3/4	.06"- .13" (1.6-3.2)	F2	Green	SHC1029	—	—	—	—
	.13"- .19" (3.2-4.7)		Orange	SHC1030	SHC1030ZP	—	—	—
	.19"- .25" (4.7-6.3)		Red	SHC1031	SHC1031ZP	—	—	—
	.25"- .38" (6.3-9.7)		White	SHC1032	SHC1032ZP	—	—	—
	.38"- .50" (9.7-12.7)		Blue	SHC1033	SHC1033ZP	—	—	—
	.50"- .63" (12.7-15.9)		Brown	SHC1034	SHC1034ZP	—	—	—
3/4	.38"- .50" (9.5-12.7)	F3	Blue	—	SHC1035ZP	SHC1035SS	SHC1035CR	SHC2035CR
	.50"- .63" (12.7-15.9)		Brown	SHC1036	—	SHC1036SS	SHC1036CR	SHC2036CR
	.63"- .75" (15.9-19.0)		Yellow	SHC1037	SHC1037ZP	SHC1037SS	SHC1037CR	SHC2037CR
	.75"- .88" (19.0-22.2)		Orchid	SHC1038**	SHC1038ZP**	SHC1038SS**	SHC1038CR**	SHC2038CR**
1	.50"- .63" (12.7-15.9)	F3	Brown	—	SHC1097ZP	—	—	—
	.63"- .75" (15.9-19.0)		Yellow	—	SHC1098ZP	—	—	—
	.75"- .88" (19.0-22.2)		Orchid	—	SHC1099ZP	—	—	—
1	.38"- .50" (9.7-12.7)	F4	Blue	SHC1039	—	—	SHC1039CR	—
	.50"- .63" (12.7-15.9)		Brown	SHC1040	—	—	SHC1040CR	SHC2040CR
	.63"- .75" (15.9-19.0)		Yellow	SHC1041	—	SHC1041SS	SHC1041CR	SHC2041CR
	.75"- .88" (19.0-22.2)		Orchid	SHC1042	—	SHC1042SS	SHC1042CR	SHC2042CR
	.88"-1.00" (22.2-25.4)		Gray	SHC1043	SHC1043ZP	SHC1043SS	SHC1043CR	SHC2043CR
	1.00"-1.13" (25.4-28.6)		Pink	SHC1044**	—	SHC1044SS**	SHC1044CR**	SHC2044CR**

Note: See pages Y-77 to Y-87 for technical information and dimensional drawings.

\*IP66 Suitability when used with optional metal clad O-ring, see page Y-74 for additional information.

\*\*Cable jacket may have to be stripped to pass through connector body.

Form 4 aluminum and plated steel nuts are machined, bodies are cast aluminum.

Locknuts sold separately. See page Y-74 for additional information.

Dimensions in Inches (mm)