

Color: Gray

UPC Code: 07847778815



5342-GY

Brand Features

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Item Description

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Gray

Technical Information

AC Horsepower Ratings At Rated Voltage: 1 HP

Electrical Specifications Grounding: Self-Grounding

Amperage: 20 A

Voltage: 125 VAC

Pole: 2 Wire: 3

Dielectric Voltage: Withstands 2000V

per UL498 Current Limiting: Full Rated Current Temperature Rise: Max 30C after 250

cycles OL at 200 percent rated current

Environmental Specifications Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 60°C

Material Specifications

Face Material: Thermoplastic Nylon

Body Material: Thermoplastic Nylon

Line Contacts: Phosphor Bronze Terminal Screws: Plated Brass

Grounding Screw: Plated Steel

Ground Clips: Brass

Strap Material: Galvanized Steel with Riveted Ground Contacts Color: Gray Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Terminal Accom.: 14-10 AWG **Product ID:** Ratings are permanently marked on device

Torque Range: 14-16 inch pounds Termination: Side Wire

Product Features

Grounding: Self-Grounding NEMA: 5-20R

Face Material: Thermoplastic Nylon Body Material: Thermoplastic Nylon Color: Gray

Device Type: Duplex Receptacle Outlet Feature 4: Smooth Face Grade: Heavy-Duty Industrial Specification Grade


<u>Standards and Certifications</u> NEMA: WD-1 & WD-6 ANSI: C-73 UL498: File E13399 UL Fed Spec WC-596: File E13399 CSA C22.2 No. 42: File 152105 NOM: 057

Warranty: 10 Year Limited



Dimensional Diagram 1.12 (28.4 mm) 1.55 (39.5 mm) 0.87 22.1 mm (0 Ο 68 æ 2.77 (70.4 mm) 4.06 (103.2 mm) (83.3 mm 3.28 68 0 1.31 (33.3 mm)

Wiring Diagram



5-20R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

