



UPC Code: 07847724031 Country Of Origin: United States

CSB1-15G

Brand Features

Leviton's Commercial Specification Grade switches are designed to offer outstanding reliability and top performance in commercial settings. Ideal applications include municipal facilities, government buildings, malls, department stores, hospital and health care facilities, office buildings, schools, colleges, universities, houses of worship and cultural institutions. Leviton offers a large selection of 15 and 20 Amp Commercial switches, available in a wide variety of colors, wiring options and other features.

Item Description

15 Amp, 120/277 Volt, Toggle Single-Pole AC Quiet Switch, Commercial Spec Grade, Grounding, Back &Side Wired, - Gray

Technical Information

AC Horsepower Ratings HP Rating: 1/2HP-120V 2HP-240V-277V

Electrical Specifications
Amperage: 15 A

Voltage: 120/277 VAC

Max. Amperage: 12 Amp Dielectric Voltage: Withstands 1500V for 1 minute

Temperature Rise: Maximum 30 degrees C rise

Environmental Specifications Flammability: Rated V-2 per UL94 Operating Temperature: -40°C to 65°C


Material Specifications Body Material: Thermoplastic Base Material: PBT Strap Material: Steel Actuator Material: Thermoplastic Toggle: Polycarbonate Cover Material: Nylon Contacts: Silver-Cadmium .031 Thick Terminal Screws: Steel 8-32 Color: Gray


Mechanical Specifications Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral Terminal Accom.: 14-#10 AWG back wired; #14-#12 AWG side wired Termination: Back or Side Wire Product ID: Stamped on Strap Torque Range: 12-14 inch pounds Product Features Voltage: 120/277 VAC HP Rating: 1/2HP-120V 2HP-240V-277V

Actuator Material: Thermoplastic Color: Gray Warranty: 10-Year Limited Grade: Commercial Specification Grade Function: Single-Pole Device Type: Toggle Switch

Standards and Certifications NEMA: WD-1 & WD-6 ANSI: C-73 UL Fed Spec WS896E: File #E7458 UL Standard: UL 20 CSA C22.2 No. 111: File #152105 NOM: 057 Warranty: 10-Year Limited

Dimensional Diagram





SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

