



## Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL Listed
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Voltage Rating	240 V AC
Wire Size	AWG 6...300 kcmil copper or aluminium

## Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	15 hp 240 V AC 50...60 Hz 3 phase NEC 240.6
Width	26.25 in (666.75 mm)
Height	32.5 in (825.50 mm)
Maximum Depth	10.63 in (270.00 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil



## Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901911746
Nbr. of units in pkg.	1
Package weight(Lbs)	77 lb(US) (34.93 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.80 in (27.432 cm)
Package 1 width	26.20 in (66.548 cm)
Package 1 Length	34.20 in (86.868 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------