

30A Twist-Lock Devices

30 Amp, 125, 250 Volts
and 277 Volts AC, 2 Pole,
3 Wire, Grounding



Plugs

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4X, 12

Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox clamps.	.325"-.930" (9-24)	HBL2611SW	HBL2621SW	—

Safety-Shroud®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Black and white nylon body, white Valox shroud. Can be used with the Insulgrip® Connector Bodies.	.360"-.930" (9-24)	HBL2611S	HBL2621S	—

Note: See page C-48 for accessories.

Insulgrip

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.360"-.930" (9-24)	HBL2611	HBL2621	HBL2631
Black and white nylon, spring termination.	.360"-.930" (9-24)	HBL2611ST	HBL2621ST	—
Heat stabilized, gray nylon, 220° F (104° C).	.360"-.930" (9-24)	HBL2611F	HBL2621F	—
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	HBL26CM11	HBL26CM21	—
All black nylon.	.360"-.930" (9-24)	HBL2611BK	HBL2621BK	—
All black nylon, spring termination.	.360"-.930" (9-24)	HBL2611STBK	HBL2621STBK	—
Cord clamps with removable inserts. All black nylon.	.360"-.930" (9-24)	—	HBL2621EBK	—

Note: See page C-53 for accessories.

Valise®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2611VY	HBL2621VY	—
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM11V	—	—
Black nylon.	.590"-.930" (15.0-23.6)	HBL2611VBK	HBL2621VBK	—

Note: See page C-53 for accessories.

Flanged Inlets

Watertight Safety-Shroud

IP66 SUITABILITY

UL Type 4X, 12

Description	Catalog Number		
Gray Valox housing and flange.	HBL2615SW	HBL2625SW	—
Reverse service, gray Valox housing and flange (use with HBL2613SR) (not shown).	HBL2615SWR	—	—

Note: See page C-54 for accessories.

Insulgrip

IP20 SUITABILITY

Description	Catalog Number		
Nylon casing, back wired.	HBL2615	HBL2625	HBL2635
Nylon casing, spring termination.	HBL2615ST	HBL2625ST	—
Heat stabilized, gray nylon, 220° F (104° C).	HBL2615F	HBL2625F	—
Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover.	HBL2615M3	—	—


Note: See page C-52 for accessories.

See pages C-69 and C-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.

See page C-74 for technical information on Valise plugs and connectors.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.


Dimensions in Inches (mm)



HBL2611SW



HBL2621S




HBL2621



HBL2611ST



HBL2615SW



HBL2625