

**EXTRA-DEEP 22.5-MM PUSHBUTTON ENCLOSURES, TYPE 4X**

**INDUSTRY STANDARDS**

 UL 508A Listed; Type 4, 4X, 12; File Number E61997  
 cUL Listed per CSA C22.2 No 94; Type 4, 4X, 12; File Number E61997

 NEMA/EEMAC Type 4X, 12, 13  
 CSA File Number 42186: Type 4, 4X, 12  
 IEC 60529, IP66

**APPLICATION**

Designed to house 22.5-mm oil-tight pushbuttons, switches and pilot lights. Enclosures provide protection against dust, dirt, oil and water. Extra-deep design accommodates additional contact blocks for pushbuttons.

**SPECIFICATIONS**

- Type 304 stainless steel
- Seams continuously welded and ground smooth
- Captivated stainless steel cover screws thread into sealed wells
- Enclosures 8.50 x 4.00 x 4.75 in. (216 x 102 x 121 mm) and larger have internal detachable hinge to hold cover open during wiring, yet permit immediate removal
- Bonding provision on door; grounding nut on body
- Oil-resistant gasket

**FINISH**

Covers and sides of body have a smooth #4 brushed finish.

**ACCESSORIES**

 Industrial Corrosion Inhibitors, page 1248  
 Hol-Sealers Hole Seals  
 Tamper-Resistant Screws

**BULLETIN: PB1S**
**Standard Product**

Catalog Number	AxBxC in./mm	Body Gauge	Cover Gauge	Holes	Mounting G x H in./mm	Overall L x W in./mm	F in./mm	K in./mm	M in./mm	T in./mm	V in./mm	Y in./mm
E1PBGXSS	4.00 x 4.00 x 4.75 102 x 102 x 121	16	16	1	4.50 x 3.13 114 x 80	5.00 x 4.22 127 x 107	3.75 95	2.00 51	4.18 106	3.75 95	5.00 127	—
E2PBGXSS	6.00 x 4.00 x 4.75 152 x 102 x 121	14	16	2	6.50 x 3.13 165 x 80	7.00 x 4.22 178 x 107	3.75 95	4.00 102	6.18 157	3.75 95	5.00 127	1.98 50
E3PBGXSS	8.00 x 4.00 x 4.75 203 x 102 x 121	14	16	3	8.50 x 3.13 216 x 80	9.00 x 4.22 229 x 107	3.75 95	6.00 152	8.18 208	3.75 95	5.00 127	1.86 47
E4PBGXSS	10.00 x 4.00 x 4.75 254 x 102 x 121	14	16	4	10.50 x 3.13 267 x 80	11.00 x 4.22 270 x 107	3.75 95	8.00 203	10.18 259	3.75 95	5.00 127	1.73 44

