

**20 Amp, 250 Volts**  
**2 Pole, 2 Wire, Non-Grounding**




**20A 250V**  
**NEMA L2-20P**  
**2 HP**

## Plugs

Description	Cord Dia.	Catalog Number
Black and white nylon, polarized, multiple drive screws.	.220"-.720" (5.6-18.3)	<b>HBL7102C</b>

Note: See page B-51 for accessories.



**HBL7102C**

## Flanged Inlets

Description	Catalog Number
Nylon casing, back wired, polarized, multiple drive screws.	<b>HBL8815C</b>

Note: See page B-50 for accessories.



**HBL8815C**



**20A 250V**  
**NEMA L2-20R**  
**2 HP**

## Connector Bodies

Description	Cord Dia.	Catalog Number
Black and white nylon, multiple drive screws.	.220"-.720" (5.6-18.3)	<b>HBL7101C</b>

Note: See page B-51 for accessories.




**HBL7101C**

## Receptacles

Description	Catalog Number
Single, black phenolic.	<b>HBL7210B</b>
Single, mounted on 4" (101.6) round box cover, black phenolic.	<b>HBL7217B</b>

Note: See pages B-50 and B-51 for accessories.



**HBL7210B**

## Flanged Receptacles


Description	Catalog Number
Insulgrip nylon casing, back wired, multiple drive screws.	<b>HBL8809C</b>
Metal flange, stainless steel casing, black phenolic, exposed terminals.	<b>HBL3226</b>

Note: See pages B-50 and B-51 for accessories.

Only receptacles and plugs are HP rated.  
 HP ratings are AC only.



**HBL8809C**



**HBL3226**

Dimensions in Inches (mm)