

2510MCW3

Manual Starter - NEMA 4 Polyester - 3P - Size M1
- No Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility



Price* : 950.40 USD



Main

Product or component type	Manual Starter
Range of product	M
NEMA size	M-1

Complementary

Control type	Push-button
Local signalling	No indicator
Motor power hp	7.5 hp at 200...230 V AC 3 phases 10 hp at 380...575 V AC 3 phases
System Voltage	600 V AC
Poles description	3P
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	3
AWG gauge	AWG 14...AWG 8 (copper)
Auxiliary contact composition	Without
Height	12.13 in
Width	6.5 in
Depth	6.41 in

Environment

Product certifications	UL listed file E42243 CCN NLRV CSA LR60905 class 3211 05
NEMA degree of protection	NEMA 4/4X glass polyester

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901821021
Nbr. of units in pkg.	1
Package weight(Lbs)	8.0099999999999998
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------