








Flush Floor Boxes and Covers





Flush Round Single or Multi-Service Non-Metallic Floor Boxes, for Use In Concrete Floors

	 PFB1
Min. Depth of Pour	3.00" (76.2)
Cubic Inch (cm ³) Capacity	100 cu. in. (1638.7 cm ³) prior to cutting level to floor (19.5 cu. in. (313.2 cm ³) per inch of depth).
Dimensions – A	6.00" (152.4)
Dimensions – B	7.08" (179.8)
Dimensions – C	6.69" (169.9)
Dimensions – D	5.38" (136.5)
Hubs	(2) 1" and (2) 3/4" Conduit Hubs
Concrete Cover Included	✓
Closure/Reducer Plugs	(2) 1" plugs close off 1" hubs or reduce 1" to 3/4" (2) 3/4" plugs close off 3/4" hubs or reduce 3/4" to 1/2"

Note: UL File Number E92074. CSA File Number LR18416.







Flush Round Covers and Flanges[†]

	SF39253A	PFBCBRA	PFBCBLA	PFBCGYA	PFBCIA
Multi-Service Cover and Flange Assemblies Includes floor box cover with duplex flaps, (2) 1/2 in. dia. low voltage feed through holes and matching carpet flange. 6.25 in. Diameter.					
	Brass	Brown Non-Metallic	Black Non-Metallic	Gray Non-Metallic	Ivory Non-Metallic

Metal Carpet Flange	Adapter Ring	Multi-Service Replacement Covers
Use with single service covers for carpet applications. 6.25 in. Diameter	Use with single service covers for tile applications.	
S3082 	S5016 	Material
Brass	Brass	Metallic
SA3082 	SA5016 	Color
Brushed Aluminum	Aluminum	Black Brown Gray Ivory
		Non-metallic
		PFBCBLA PFBCBRA PFBCGYA PFBCIA

Note: *Replacement galvanized steel ring use part number S5016PG

Single Service Covers[†]

Brass Aluminum 3.88 in. Dia.	S3925 SA3925 	S3725 SA3725 	S2525 SA2525 	S2725 SA2725 	S2925 SA2925 	S3525 – 	S3325 – 	S3913 SA3913 
	Duplex Flap	Duplex Screw	2-1/8" x 3/4" Combination	2-1/8" x 1" Combination	2-1/8" Single Receptacle	2-3/8" Single Receptacle	2-3/8" Single Receptacle (Terrazzo Floor)	Blank

One Piece Brass Cover and Carpet Flange[†]

Brass Aluminum 6.25 in. Dia.	SF3925* SFA3925* 	SFB3926** SFA3926 	SF2525* – 	SF2725* – 	SF2925* – 
	Duplex Flap	Style Line [®] Decorator Opening	2-1/8" x 3/4" Combination	2-1/8" x 1" Combination	2-1/8" Single Receptacle

*Note: Adapter ring S5016 is required for mounting SF series covers onto PFBA1A.





**Note: Brass plated aluminum

Note: [†]COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor; Non-metallic covers and flanges 300 lbs. Load applied through a 3 in. (76) mandrel at the center of the cover. Dimensions in Inches (mm)

ScrubShield[®] cULus SP[®]

Complies with UL514A

Catalog Number

Adapter Required for all applications.		PFBA1A
Low Voltage Divider Required for use with catalog number PFB1 when used in multi-service applications. Accepts Hubbell standard duplex receptacles or 15A Twist-Lock [®] duplex receptacles (HBL4700 series).		PFBT1A
"Y" Adapter 3/4 in. "Y" adapter to feed parallel runs of 3/4 in. conduit.		PFBYA1
Pre-pour PVC stand increases PFB1 box height 2.5 in. to 4.0 in. within the concrete pour.		PFBSTANDGY