


Flush Rectangular Cast Iron Floor Boxes with Metal Covers, for Use In Concrete Floors

Style	Cast Iron					
	1-Gang Deep	2-Gang Deep	3-Gang Deep	1-Gang Shallow	2-Gang Shallow	3-Gang Shallow
						
Catalog Numbers	FB4133*	FB4233	FB4333	FB4114*	FB4214	FB4314
Cover Frame Material	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic	Thermoplastic
Min. Depth of Pour	3.50" (95.3)	3.50" (95.3)	3.50" (95.3)	2.00" (50.8)	2.00" (50.8)	2.00" (50.8)
Adjustability	Fully	Fully	Fully	Semi	Semi	Semi
Before Pour External Height Adjustment	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)	1.25" (31.8)
After Pour Internal Height Adjustment	.875" (22.2)	.875" (22.2)	.875" (22.2)	—	—	—
Cubic Inch (cm3) Capacity per Gang	33.0 (540.8)	36.5 (598.2)	36.5 (598.2); 34.8 (570.3) center gang	16.0 (262.2)	16.0 (262.2)	16.0 (262.2)
Dimensions – A	3.42" (87.0)	3.40" (86.4)	3.40" (86.4)	2.03" (51.4)	2.05" (51.9)	2.06" (52.2)
Dimensions – B	4.85" (123.2)	4.91" (124.7)	4.91" (124.7)	5.66" (143.7)	5.46" (138.7)	5.46" (138.7)
Dimensions – C	4.85" (123.2)	8.13" (206.5)	11.41" (289.8)	4.38" (111.3)	7.50" (190.4)	10.71" (272.0)
Dimensions – D	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)	4.32" (109.7)
Dimensions – E	3.20" (81.3)	6.42" (163.0)	9.64" (244.8)	3.20" (81.3)	6.42" (163.0)	9.64" (244.8)
Threaded Hubs	(4) 1"	(6) 1"	(8) 1"	(4) ¾"	(4) ¾"	(6) ¾"
Concrete Cover Included	✓	✓	✓	✓	✓	✓
Closure Plugs Included	✓	✓	✓	✓	✓	✓
1" to 3/4" Threaded Reducer	2 Each	4 Each	4 Each	—	—	—
Low Voltage Barrier	—	(1) Removable	(2) Removable	—	Non-Removable	Non-Removable

Note: UL File Number E92074. CSA File Number LR18416. *Suitable for single service applications only.

Flush Rectangular Covers Flanges

Required Components for Flush Tile or Finished Concrete Applications




Brass **S5017GR** Adapter Frame with Grounding Wire (One required per gang) Dim. 4.36" x 3.20" x 0.30"
Aluminum **SA5017GR**



Flat Flanges*

Flat Flange Height 0.125"

Number of Gangs	1-Gang	2-Gang	3-Gang
Dimensions	6.00" x 4.85"	6.00" x 8.13"	6.00" x 11.34"
Brass, square edge	SB3083W	SB3084W	SB3085W
Aluminum, square edge	SA3083W	SA3084W	SA3085W
Brass, beveled edge	SB3083WB	SB3084WB	SB3085WB
Aluminum, beveled edge	SA3083WB	SA3084WB	SA3085WB



*Flange applications; square edge for carpet and recessed, beveled edge for use on hard finished surfaces

Covers – One Required per Gang†

Brass	S3825	S3625	S3625TR	S3826	S2425	S2625	S2825	S3425	S3813
Aluminum	SA3825	SA3625	SA3625TR	SA3826	SA2425	SA2625	—	—	SA3813
Dimensions 4.15" x 2.99"									
	Duplex Flap	Duplex Screw	Tamper Resistant Duplex Screw	Style Line® Decorator Opening	2 1/8" x 3/4" Combination	2 1/8" x 1" Combination	2 1/8" Single Receptacle	2 3/8" Single Receptacle	Blank

†COVER LOAD RATING; Metallic covers and flanges 2,000 lbs. with 2x safety factor. Load applied through a 3 in. (76) mandrel at the center of the cover.

Dimensions in Inches (mm)